6

Safety Break-away Coupling - Breaking Bolt Series Industrial Version - Female NPT x Female NPT

Application:

 suitable for LP Gas service, designed to be installed between a fixed point (pipe, pump, manifold) and a hose

Features:

- coupling automatically senses an excessive load, closes the valves and disconnects
- high flow rate / low pressure drop
- working pressure: 360 PSI at ambient temperature (70°F)
- female NPT is standard, optional ANSI / DIN flanges or male NPT are available
- · FKM is standard seal





LP Gas Hose Caps and Plugs

Metal Acme Caps





Female Acme Thread	Description	Material	Part #	Price/E
13/4"	cap with ring and chain	brass	ME229-1	\$67.70
13/4"	cap with ring and chain	steel	ME229S-1	115.15
21/4"	cap with knob plug and chain	brass	ME431F-1	170.90
21/4"	cap with knob plug, ring, chain	steel	ME431FS-1	193.05
31/4"	cap knob with ring and chain	brass	ME441F-1	258.35
31/4"	cap with knob plug, ring and chain	steel	ME441FS-1	282.95

Plastic Acme Caps





ME109-1 ME109-NH3-1

Female Acme Thread	Description	Plastic Part #	Price/E
13/4"	cap with ring and chain, yellow	ME109-1	\$8.10
13/4"	cap with chain assembly, for any hydrous service	ME109-NH3-1	9.20







ME179-1 ME180-1

ME181-1

Male Acme Thread	Description	Plastic Part #	Price/E
13/4"	plug with dust seal and chain assembly, yellow	ME179-1	\$30.45
21/4"	plug with dust seal and chain assembly, yellow	ME180-1	37.15
31/4"	plug with dust seal and chain assembly, yellow	ME181-1	81.60