



King Crimp Style Sleeves



Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon products.

Hose ID	Hose OD		Carbon Steel		304 Stainless Steel		Aluminum		Work. Pressure (PSI)		Sleeve ID	Sleeve Wall Thick.	Sleeve Overall Length
	From	To	Part #	Price	Part #	Price	Part #	Price	cam & groove ¹	KC nipple ²			
1"	1-13/64"	1-16/64"	CS100-1CS	\$4.70	CS100-1SS	\$7.15	---	---	*	*	1.313"	.062"	2½"
	1-17/64"	1-20/64"	CS100-2CS	4.70	CS100-2SS	7.15	CS100-2AL	\$7.60	*	*	1.375"	.062"	2½"
	1-21/64"	1-24/64"	CS100-3CS	4.70	CS100-3SS	7.15	---	---	*	*	1.438"	.062"	2½"
	1-25/64"	1-28/64"	CS100-4CS	4.70	CS100-4SS	7.15	CS100-4AL	7.60	*	*	1.500"	.062"	2½"
	1-29/64"	1-32/64"	CS100-5CS	4.70	CS100-5SS	7.15	---	---	*	*	1.563"	.062"	2½"
	1-33/64"	1-36/64"	CS100-6CS	4.70	CS100-6SS	7.15	CS100-6AL	7.60	*	*	1.625"	.062"	2½"
	1-37/64"	1-40/64"	CS100-7CS	4.70	CS100-7SS	7.15	---	---	*	*	1.688"	.062"	2½"
	1-41/64"	1-44/64"	CS100-8CS	4.70	CS100-8SS	7.15	---	---	*	*	1.750"	.062"	2½"
	1-45/64"	1-48/64"	CS100-9CS	4.70	CS100-9SS	7.15	---	---	*	*	1.813"	.062"	2½"
	1-49/64"	1-52/64"	CS100-10CS	4.70	CS100-10SS	7.15	---	---	*	*	1.875"	.062"	2½"
1¼"	1-41/64"	1-44/64"	CS125-3CS	4.80	CS125-3SS	8.60	---	---	250	300	1.750"	.060"	2-5/8"
	1-45/64"	1-48/64"	CS125-4CS	4.80	CS125-4SS	8.60	---	---	250	300	1.813"	.060"	2-5/8"
	1-49/64"	1-52/64"	CS125-5CS	4.80	CS125-5SS	8.60	---	---	250	300	1.875"	.060"	2-5/8"
	1-53/64"	1-56/64"	CS125-6CS	4.80	CS125-6SS	8.60	---	---	250	300	1.938"	.060"	2-5/8"
1½"	1-41/64"	1-44/64"	CS150-1CS	4.85	CS150-1SS	8.50	---	---	250	300	1.750"	.062"	2½"
	1-45/64"	1-48/64"	CS150-2CS	4.85	CS150-2SS	8.50	---	---	250	300	1.813"	.062"	2½"
	1-49/64"	1-52/64"	CS150-3CS	4.85	CS150-3SS	8.50	CS150-3AL	10.00	250	300	1.875"	.062"	2½"
	1-53/64"	1-56/64"	CS150-4CS	4.85	CS150-4SS	8.50	---	---	250	300	1.938"	.062"	2½"
	1-57/64"	1-60/64"	CS150-5CS	4.85	CS150-5SS	8.50	---	---	250	300	2.000"	.062"	2½"
	1-61/64"	2"	CS150-6CS	4.85	CS150-6SS	8.50	---	---	250	300	2.063"	.062"	2½"
	2-1/64"	2-4/64"	CS150-7CS	4.85	CS150-7SS	8.50	CS150-7AL	10.00	250	300	2.125"	.062"	2½"
	2-5/64"	2-8/64"	CS150-8CS	4.85	CS150-8SS	8.50	---	---	250	300	2.188"	.062"	2½"
	2-9/64"	2-12/64"	CS150-9CS	4.85	CS150-9SS	8.50	---	---	250	300	2.250"	.062"	2½"
	2-13/64"	2-16/64"	CS150-10CS	4.85	CS150-10SS	8.50	---	---	250	300	2.313"	.062"	2½"
	2-17/64"	2-20/64"	CS150-11CS	4.85	CS150-11SS	8.50	---	---	250	300	2.375"	.062"	2½"
	2-21/64"	2-24/64"	CS150-12CS	4.85	CS150-12SS	8.50	---	---	250	300	2.438"	.062"	2½"
2"	2-13/64"	2-16/64"	CS200-1CS	5.70	CS200-1SS	11.75	---	---	250	250	2.313"	.062"	2-7/8"
	2-17/64"	2-20/64"	CS200-2CS	5.70	CS200-2SS	11.75	---	---	250	250	2.375"	.062"	2-7/8"
	2-21/64"	2-24/64"	CS200-3CS	5.70	CS200-3SS	11.75	---	---	250	250	2.438"	.062"	2-7/8"
	2-25/64"	2-28/64"	CS200-4CS	5.70	CS200-4SS	11.75	CS200-4AL	12.70	250	250	2.500"	.062"	2-7/8"
	2-29/64"	2-32/64"	CS200-5CS	5.70	CS200-5SS	11.75	---	---	250	250	2.563"	.062"	2-7/8"
	2-33/64"	2-36/64"	CS200-6CS	5.70	CS200-6SS	11.75	---	---	250	250	2.625"	.062"	2-7/8"
	2-37/64"	2-40/64"	CS200-7CS	5.70	CS200-7SS	11.75	---	---	250	250	2.688"	.062"	2-7/8"
	2-41/64"	2-44/64"	CS200-8CS	5.70	CS200-8SS	11.75	---	---	250	250	2.750"	.062"	2-7/8"
	2-45/64"	2-48/64"	CS200-9CS	5.70	CS200-9SS	11.75	---	---	250	250	2.813"	.062"	2-7/8"
	2-49/64"	2-52/64"	CS200-10CS	5.70	CS200-10SS	11.75	CS200-10AL	12.70	250	250	2.875"	.062"	2-7/8"
	2-53/64"	2-56/64"	CS200-11CS	5.70	CS200-11SS	11.75	---	---	250	250	2.938"	.062"	2-7/8"
	2-57/64"	2-60/64"	CS200-12CS	5.70	CS200-12SS	11.75	---	---	250	250	3.000"	.062"	2-7/8"

* consult Dixon for pressure rating

¹ based on using crimp cam and groove shanks

² based on using King combination nipples