

King Crimp Style Ferrules



Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon products.

Hose ID	Hose OD		Carbon Steel		304 Stainless Steel		Work. Pressure (PSI)		Ferrule ID	Ferrule Wall Thickness	Ferrule Overall Length
	From	To	Part #	Price	Part #	Price	cam & groove ¹	KC nipple ²			
1"	1-13/64"	1-16/64"	CF100-1CS	\$10.00	CF100-1SS	\$10.15	*	*	1.313"	.062"	2-13/16"
	1-17/64"	1-20/64"	CF100-2CS	10.00	CF100-2SS	10.15	*	*	1.375"	.062"	2-13/16"
	1-21/64"	1-24/64"	CF100-3CS	10.00	CF100-3SS	10.15	*	*	1.438"	.062"	2-13/16"
	1-25/64"	1-28/64"	CF100-4CS	10.00	CF100-4SS	10.15	*	*	1.500"	.062"	2-13/16"
	1-29/64"	1-32/64"	CF100-5CS	10.00	CF100-5SS	10.15	*	*	1.563"	.062"	2-13/16"
	1-33/64"	1-36/64"	CF100-6CS	10.00	CF100-6SS	10.15	*	*	1.625"	.062"	2-13/16"
	1-37/64"	1-40/64"	CF100-7CS	10.00	CF100-7SS	10.15	*	*	1.688"	.062"	2-13/16"
	1-41/64"	1-44/64"	CF100-8CS	10.00	CF100-8SS	10.15	*	*	1.750"	.062"	2-13/16"
	1-45/64"	1-48/64"	CF100-9CS	10.00	CF100-9SS	10.15	*	*	1.813"	.062"	2-13/16"
	1-49/64"	1-52/64"	CF100-10CS	10.00	CF100-10SS	10.15	*	*	1.875"	.062"	2-13/16"
1 1/4"	1 41/64"	1-44/64"	CF125-3CS	10.25	CF125-3SS	12.00	250	350	1.750"	.060"	2-13/16"
	1 45/64"	1-48/64"	CF125-4CS	10.25	CF125-4SS	12.00	250	350	1.813"	.060"	2-13/16"
	1 49/64"	1-52/64"	CF125-5CS	10.25	CF125-5SS	12.00	250	350	1.875"	.060"	2-13/16"
	1 53/64"	1-56/64"	CF125-6CS	10.25	CF125-6SS	12.00	250	350	1.938"	.060"	2-13/16"
1 1/2"	1-41/64"	1-44/64"	CF150-1CS	11.40	CF150-1SS	15.60	250	350	1.750"	.062"	2-13/16"
	1-45/64"	1-48/64"	CF150-2CS	11.40	CF150-2SS	15.60	250	350	1.813"	.062"	2-13/16"
	1-49/64"	1-52/64"	CF150-3CS	11.40	CF150-3SS	15.60	250	350	1.875"	.062"	2-13/16"
	1-53/64"	1-56/64"	CF150-4CS	11.40	CF150-4SS	15.60	250	350	1.938"	.062"	2-13/16"
	1-57/64"	1-60/64"	CF150-5CS	11.40	CF150-5SS	15.60	250	350	2.000"	.062"	2-13/16"
	1-61/64"	2"	CF150-6CS	11.40	CF150-6SS	15.60	250	350	2.063"	.062"	2-13/16"
	2-1/64"	2-4/64"	CF150-7CS	11.40	CF150-7SS	15.60	250	350	2.125"	.062"	2-13/16"
	2-5/64"	2-8/64"	CF150-8CS	11.40	CF150-8SS	15.60	250	350	2.188"	.062"	2-13/16"
	2-9/64"	2-12/64"	CF150-9CS	11.40	CF150-9SS	15.60	250	350	2.250"	.062"	2-13/16"
	2-13/64"	2-16/64"	CF150-10CS	11.40	CF150-10SS	15.60	250	350	2.313"	.062"	2-13/16"
	2-17/64"	2-20/64"	CF150-11CS	11.40	CF150-11SS	15.60	250	350	2.375"	.062"	2-13/16"
	2-21/64"	2-24/64"	CF150-12CS	11.40	CF150-12SS	15.60	250	350	2.438"	.062"	2-13/16"
2"	2-13/64"	2-16/64"	CF200-1CS	12.95	CF200-1SS	17.65	250	300	2.313"	.062"	3-1/8"
	2-17/64"	2-20/64"	CF200-2CS	12.95	CF200-2SS	17.65	250	300	2.375"	.062"	3-1/8"
	2-21/64"	2-24/64"	CF200-3CS	12.95	CF200-3SS	17.65	250	300	2.438"	.062"	3-1/8"
	2-25/64"	2-28/64"	CF200-4CS	12.95	CF200-4SS	17.65	250	300	2.500"	.062"	3-1/8"
	2-29/64"	2-32/64"	CF200-5CS	12.95	CF200-5SS	17.65	250	300	2.563"	.062"	3-1/8"
	2-33/64"	2-36/64"	CF200-6CS	12.95	CF200-6SS	17.65	250	300	2.625"	.062"	3-1/8"
	2-37/64"	2-40/64"	CF200-7CS	12.95	CF200-7SS	17.65	250	300	2.688"	.062"	3-1/8"
	2-41/64"	2-44/64"	CF200-8CS	12.95	CF200-8SS	17.65	250	300	2.750"	.062"	3-1/8"
	2-45/64"	2-48/64"	CF200-9CS	12.95	CF200-9SS	17.65	250	300	2.813"	.062"	3-1/8"
	2-49/64"	2-52/64"	CF200-10CS	12.95	CF200-10SS	17.65	250	300	2.875"	.062"	3-1/8"
	2-53/64"	2-56/64"	CF200-11CS	12.95	CF200-11SS	17.65	250	300	2.938"	.062"	3-1/8"
	2-57/64"	2-60/64"	CF200-12CS	12.95	CF200-12SS	17.65	250	300	3.000"	.062"	3-1/8"

* consult Dixon for pressure rating

¹ based on using crimp cam and groove shanks

² based on using King combination nipples