# Clamp Gaskets Silicone Flanged Clamp Gaskets - White




Type 2 - Flanged and la ge

#### Features:

- color code: pink dot
- peroxide cured
- meets 21CFR 177.2600
- passed USP Class VI Cytotoxicity testing
- not recommended for use with bolted clamps

Part #	Price/E
40MPF-XW100	\$4.50
40MPF-XW150	4.70
40MPF-XW200	4.70
40MPF-XW250	5.80
40MPF-XW300	6.95
40MPF-XW400	9.15
40MPF-XW600	48.50
40MPF-XW800	60.30
40MPF-XW1000	75.15
40MPF-XW1200	77.30
	40MPF-XW100 40MPF-XW150 40MPF-XW200 40MPF-XW250 40MPF-XW300 40MPF-XW400 40MPF-XW600 40MPF-XW800 40MPF-XW1000

## Buna-N Mesh Screen Clamp Gasket, 316



Type 3 - Mesh

### Features:

- color code: red dot
- meets 21CFR 177.2600
- 10 mesh standard, other mesh available-call for details

Size	Part #	Price/E
1"	40MPS-U100	\$47.10
1½"	40MPS-U150	41.45
2"	40MPS-U200	44.35
2½"	40MPS-U250	58.85
3"	40MPS-U300	67.75
4"	40MPS-U400	105.95

## PTFE Envelope Clamp Gaskets with EPDM Filler



## Features:

- color code: usually not marked peroxide cured EPDM meets 21CFR 177.1550
- PTFE passed USP Class VI Cytotoxicity testing

Size	Part #	Price/E
1/2"	42MP-GRE50	\$14.90
1"	40MP-GRE100	8.15
1½"	40MP-GRE150	7.25
2"	40MP-GRE200	7.65
2½"	40MP-GRE250	9.80
3"	40MP-GRE300	10.80
4"	40MP-GRE400	19.90
6"	40MP-GRE600	69.65



PTFE is a material subject to plastic flow. When cycled through heat and then cooled down in process lines, PTFE gaskets will not return to the original configuration and it will continue to compress as the cycling continues. This plastic flow will allow leakage if clamp torques are not maintained.

# PTFE Envelope Clamp Gaskets with FKM Filler



### Features:

- color code: FKM usually not marked
- peroxide cured FKM
- meets 21CFR 177.1550
- PTFE passed USP Class VI Cytotoxicity testing

Size	Part #	Price/E
1"	40MP-GR100	\$7.40
1½"	40MP-GR150	7.25
2"	40MP-GR200	8.25
2½"	40MP-GR250	10.85
3"	40MP-GR300	11.45
4"	40MP-GR400	18.35
6"	40MP-GR600	87.80



PTFE is a material subject to plastic flow. When cycled through heat and then cooled down in process lines, PTFE gaskets will not return to the original configuration and it will continue to compress as the cycling continues. This plastic flow will allow leakage if clamp torques are not maintained.

See pages 451-452 for sizing charts.