### Forest Green Constant Flow Nozzle

#### Features:

- shatterproof and UV resistant polycarbonate is able to withstand tough environmental conditions
- · seals used for true water shut off
- easy twist spray pattern adjustment
- sold in case quantity only, with display
- 25 nozzles per case

Throad	45° Spray GPM	Plastic	\\/\/\	
Thread	@ 100 PSI	Part #	Price/E	Wt. Lbs.
¾" GHT	25.1	FNB75GHT-GD	\$493.00	10.3



## Green Constant Flow Nozzle with Bumper

#### Features:

- green plastic body with steel stem
- can be used as a replacement nozzle in the display case GNB75GHT-GD

Thread	45° Spray GPM	Plastic		Wt. Lbs.
	@ 100 PSI	Part #	Price/E	WI. LDS.
3/4" GHT	8	GNB75GHT	\$20.30	0.36



### Red Plain Hose Nozzles

#### Feature:

maximum operating pressure: 100 PSI (water only) at 70°F (21°C)

Size Thread	Thread	Length	Orifice	Red Polycarbonate		Wt. Lbs.
	Tilleau			Part #	Price/E	VVI. LDS.
1½"	NPSH	10"	1/2"	PN15	\$18.00	0.22
1½"	NST (NH)	10"	1/2"	PN15F	18.00	0.19



# Ball Shutoff Nozzle - Bolted Style

#### Features:

- rugged and lightweight
- cast aluminum body with pistol grip
- hardcoated female swivel inlet and male outlet
- maximum operating pressure: 200 PSI (water only) at 70°F (21°C)

Size	Thread	Waterway	Cast Aluminum		Wt. Lbs.
			Part #	Price/E	VVI. LDS.
1½"	NST (NH)	13/8"	ACPSO150F	\$355.00	2.9
1½"	NPSH	13/8"	ACPSO150	355.00	2.9



## Tips for Bolted Style Ball Shutoff Nozzles

### Features:

- lightweight construction
- maximum operating pressure: **200 PSI** (water only) at 70°F (21°C)
- · other orifice sizes available

Size	Thread	Length	Orifice	Anodized Aluminum		Wt. Lbs.
				Part #	Price/E	VVI. LDS.
1"	NPSH	4"	1/2"	ANT100	\$235.00	0.5
	NST (NH)	43/4"		ANT100F	235.00	0.7
1½"	NPSH	4"	1/2"	ANT150	235.00	0.5
	NST (NH)	43/4"		ANT150F	235.00	0.7



NPSH shutoff nozzle tip



NH shutoff nozzle tip

)