

## 500# Single Jacket All Polyester Fire Hose

### Features:

- outer construction: single jacket, all polyester
- tube construction: EPDM rubber lining
- proof pressure: **500 PSI**
- service test pressure: **250 PSI** at ambient temperature (70°F)
- working pressure: **225 PSI** at ambient temperature (70°F)
- consult Dixon for pricing and availability of 75' lengths, U/L labeled hoses and other threads and configurations

### Uncoupled

| Size | Bowl     | Length | Part #            | Price/E         |
|------|----------|--------|-------------------|-----------------|
| 1"   | 1-1/4"   | 50'    | <b>A510-50UC</b>  | <b>\$158.85</b> |
| 1"   | 1-1/4"   | 100'   | <b>A510-100UC</b> | <b>317.70</b>   |
| 1½"  | 1-3/4"   | 50'    | <b>A515-50UC</b>  | <b>191.05</b>   |
| 1½"  | 1-3/4"   | 100'   | <b>A515-100UC</b> | <b>382.10</b>   |
| 2½"  | 2-13/16" | 50'    | <b>A525-50UC</b>  | <b>322.40</b>   |
| 2½"  | 2-13/16" | 100'   | <b>A525-100UC</b> | <b>644.80</b>   |



### Coupled with female and male expansion ring couplings

| Size | Length | Part #         | Rocker Lug Aluminum NST (NH) RAF | Rocker Lug Brass NST (NH) RBF | Pin Lug Brass NST (NH) PBF | Rocker Lug Aluminum NPSH RAS | Rocker Lug Aluminum RA <sup>1</sup> |
|------|--------|----------------|----------------------------------|-------------------------------|----------------------------|------------------------------|-------------------------------------|
| 1"   | 50'    | <b>A510-50</b> | ---                              | ---                           | ---                        | <b>\$275.95</b>              | ---                                 |
| 1"   | 100'   | <b>A510100</b> | ---                              | ---                           | ---                        | <b>464.75</b>                | ---                                 |
| 1½"  | 25'    | <b>A515-25</b> | <b>\$205.30</b>                  | ---                           | ---                        | <b>205.30</b>                | ---                                 |
| 1½"  | 50'    | <b>A515-50</b> | <b>281.45</b>                    | <b>\$324.25</b>               | <b>\$377.30</b>            | <b>281.45</b>                | ---                                 |
| 1½"  | 100'   | <b>A515100</b> | <b>462.10</b>                    | <b>504.25</b>                 | <b>536.45</b>              | <b>462.10</b>                | ---                                 |
| 2½"  | 25'    | <b>A525-25</b> | <b>339.05</b>                    | ---                           | ---                        | <b>339.05</b>                | <b>POR</b>                          |
| 2½"  | 50'    | <b>A525-50</b> | <b>472.15</b>                    | <b>612.25</b>                 | <b>645.00</b>              | <b>472.15</b>                | <b>POR</b>                          |
| 2½"  | 100'   | <b>A525100</b> | <b>774.25</b>                    | <b>904.70</b>                 | <b>1050.60</b>             | <b>774.25</b>                | <b>POR</b>                          |



- <sup>1</sup> Customer Thread (*must specify*) refer to legend on page 566  
Consult Dixon for pricing and availability for any of the following features:
- other threads and configurations

## 500# Single Jacket All-Polyester Fire Hose - UL labeled

### Features:

- outer construction: single jacket, all polyester
- tube construction: EPDM rubber lining
- proof pressure: **500 PSI**
- service test pressure: **250 PSI** at ambient temperature (70°F)
- working pressure: **225 PSI** at ambient temperature (70°F)
- Underwriters Listed
- consult Dixon for pricing and availability of impregnated hose and other lengths threads and configurations

### Coupled with female and male expansion ring couplings

| Size | Bowl             | Length | NST Thread Part #  | NPSH Thread Part # | Price/E         |
|------|------------------|--------|--------------------|--------------------|-----------------|
| 1½"  | combo lug, brass | 50'    | <b>A515U50CBF</b>  | <b>A515U50CBS</b>  | <b>\$371.30</b> |
| 1½"  | combo lug, brass | 75'    | <b>A515U75CBF</b>  | <b>A515U75CBS</b>  | <b>POR</b>      |
| 1½"  | combo lug, brass | 100'   | <b>A515U100CBF</b> | <b>A515U100CBS</b> | <b>POR</b>      |
| 2½"  | combo lug, brass | 50'    | <b>A525U50CBF</b>  | ---                | ---             |



P