

500# All Polyester Rack Hose - Aluminum Couplings UL Labeled

Application:

- for pin rack service / emergency fire fighting only, not to be used for washdown

**Features:**

- outer construction: single jacket, all polyester
- tube construction: clear thermoplastic
- proof pressure: **300 PSI** at ambient temperature (70°F)
- service test pressure: **150 PSI** at ambient temperature (70°F)
- working pressure: **135 PSI** at ambient temperature (70°F)
- Underwriters Listed

Coupled with female and male aluminum rocker lug expansion ring couplings

Size	Length	Thread	Folded Part #	Price	Coiled Part #	Price
1½"	50'	NST (NH)	R515U50RAF/F	\$246.65	R515U50RAF	\$246.65
1½"	50'	NPSH	R515U50RAS/F	246.65	R515U50RAS	246.65
1½"	100'	NST (NH)	R515U100RAF/F	442.45	R515U100RAF	442.45
1½"	100'	NPSH	R515U100RAS/F	442.45	R515U100RAS	442.45



folded



coiled

500# All Polyester Rack Hose - Aluminum Couplings non-UL Labeled

Application:


- for pin rack service / emergency fire fighting only, not to be used for washdown

**Features:**

- outer construction: single jacket, all polyester
- tube construction: clear thermoplastic
- proof pressure: **500 PSI**
- service test pressure: **250 PSI** at ambient temperature (70°F)
- working pressure: **225 PSI** at ambient temperature (70°F)

Coupled with female and male aluminum rocker lug expansion ring couplings

Size	Length	Thread	Folded Part #	Price	Coiled Part #	Price
1½"	50'	NST (NH)	R515-50RAF/F	\$217.35	R515-50RAF	\$217.35
1½"	50'	NPSH	R515-50RAS/F	217.35	R515-50RAS	217.35
1½"	100'	NST (NH)	R515100RAF/F	342.80	R515100RAF	342.80
1½"	100'	NPSH	R515100RAS/F	342.80	R515100RAS	342.80



folded



coiled

P