


Domestic Ball Cone Check Valves

Application:

- For use with water, oil, air lines or inert gases. Not recommended for use on or near reciprocating pumps or other similar vibration causing machinery.

Features:

- tight shut-off with liquid media
- no radial alignment necessary
- straight through and streamlined for minimum change in velocity
- Reinforced TFE check is spring loaded for fast seating action.
- pressure rating: **400 PSI** WOG, cold non-shock; **125 PSI** saturated steam
- cracking pressure: .5 PSI
- temperature range: **-20°F to 353°F**



Pressure Ratings

Temperature	Pressure WOG (PSI)
-20°F to 100°F	400
200°F	200
250°F	160
275°F	150
300°F	140
325°F	130
353°F	125

female NPT x female NPT



Size	Brass		316 Stainless Steel	
	Part #	Price/E	Part #	Price/E
1/4"	61-101	\$62.00	62-101	\$133.00
3/8"	61-102	62.00	62-102	133.00
1/2"	61-103	62.00	62-103	156.90
3/4"	61-104	88.00	62-104	251.60
1"	61-105	119.00	62-105	342.50
1 1/4"	61-106	210.00	62-106	479.50
1 1/2"	61-107	268.00	62-107	650.00
2"	61-108	440.00	62-108	1120.00
2 1/2"	61-109	890.00	---	---
3"	61-100	1488.00	---	---

male NPT x female NPT



Size	Brass	
	Part #	Price/E
1/4"	61-201	\$82.00
3/8"	61-202	82.00
1/2"	61-203	82.00
3/4"	61-204	107.00
1"	61-205	155.00
1 1/4"	61-206	262.00
1 1/2"	61-207	330.00
2"	61-208	550.00