

Dixon Diesel and Gasoline Nozzles

FuelMaster™ Diesel Nozzles



Features:

- Provides the high flow capacity required by many truck stops and terminal operations.
- Micro-touch valve provides smooth operation and exceptional flow control.
- super tough nylon hand guard and hold-open clip
- easy to change 'locknut style' spout assembly
- green scuff guard

- automatic shutoff
- Underwriter's Listed
- not designed for use with small 12 volt pumps, AC utility pumps, farm pumps or consumer pumps
- These nozzles are not to be used with gravity flow tanks.*

diesel nozzle
DFN100HFdiesel nozzle
DFN100SF

| NPT Inlet | Spout Outlet | Weight (lbs) | Approximate Flow Rate at 20 PSI (GPM) | Part # | Price/E |
|-----------|--------------|--------------|---------------------------------------|-----------------|-----------------|
| 1" | 1-3/16" | 3.5 | 30 | DFN100HF | \$212.50 |
| 1" | 1-3/16" | 3.6 | 45 | DFN100SF | 295.50 |

Big Mouth™ Diesel Nozzle



Features:

- Micro-touch valve allows precise flow control
- Roto-matic latch pin provides positive auto shut-off
- pure PTFE packing eliminates stem leaks
- Super tough nylon hold-open clip and hand guard bend, but won't break.
- Snap-on handle cover makes changing scuff guards easy.

- yellow scuff guard
- automatic shutoff
- Underwriter's Listed
- not designed for use with small 12 volt pumps, AC utility pumps, farm pumps or consumer pumps
- This nozzle is not to be used with gravity flow tanks.*



| NPT Inlet | Spout Outlet | Weight (lbs) | Approximate Flow Rate at 20 PSI (GPM) | Part # | Price/E |
|-----------|--------------|--------------|---------------------------------------|---------------|-----------------|
| 1" | 1 1/8" | 3 | 20 | DFN100 | \$167.00 |

Farm and Consumer Nozzles



Features:

- Automatic fuel nozzle designed for use with small 12 volt and AC utility pumps as well as large farm and consumer pumps.
- Heavy duty, stronger and more secure hook makes it easy to hang the nozzle on the pump.

- black scuff guard on gasoline nozzle, green scuff guard on diesel nozzle
- Underwriter's Listed
- automatic shutoff
- These nozzles are not to be used with gravity flow tanks.*



gasoline nozzle



diesel nozzle

| NPT Inlet | Spout Outlet | Weight (lbs) | Approximate Flow Rate at 20 PSI (GPM) | Service | Part # | Price/E |
|-----------|--------------|--------------|---------------------------------------|----------|----------------|-----------------|
| 3/4" | 13/16" | 2 1/2 | 14 | gasoline | DN7UOBF | \$120.80 |
| 3/4" | 15/16" | 2 1/2 | 14 | diesel | DN7LOBF | 120.80 |

DEF Automatic Shutoff Nozzle

NEW

Features:

- Automatic shutoff nozzle designed for diesel exhaust fluid.
- aluminum body double coated inside and out with PTFE baked on at 500°F

- stainless steel spout
- maximum operating pressure: **50 PSI**
- wetted parts: stainless, acetal, PTFE
- FKM-A seals



| BSPP Inlet | Spout Outlet | Weight (lbs) | Approximate Flow Rate at 20 PSI (GPM) | Part # | Price/E |
|------------|--------------|--------------|---------------------------------------|----------------|-----------------|
| 3/4" | 13/16" | 2 1/2 | 14 | DEFN075 | \$484.85 |

Fuel Nozzle Part Number Cross Reference

| Dixon | M. Carder | OPW | Emco | Husky | Catlow |
|----------|---------------|------------|---------|-------------|---------|
| DN7UOBF | N7UOBF | 1AF-40FS | A2501F | XSF-33704 | NENLF |
| DN7LOBF | N7LOBF | 11APF-40FS | A2501LF | --- | NELF |
| DFN100HF | N4-Fuelmaster | 7H | A6000 | V111-173310 | MAX1 |
| DFN100 | N3-BigMouth | N/A | N/A | 1HS.026810 | MAC-1AH |