


Dixon High Flow Fuel Nozzles Fueler 100™ Nozzles



Application:

for fueling trucks, buses, off-road equipment and fuel oil delivery

Features:

- These nozzles are not to be used with gravity flow tanks. 
- machined grooves in the spout are designed to hold nozzle more securely in the fill pipe
- high flow, heavy duty automatic nozzle

NPT Inlet	Spout Size	Wt (lbs)	Approx. Flow Rate at 20 PSI (GPM)	Part #	Price/E
1½"	1¾"	6.9	50	DNOG6	\$766.80
				DNOG6RB	545.25

rebuilt Fueler 100™ nozzle

Dixon Diesel and Gasoline Nozzles Accessories

Single Plane Hose Swivels



Features:

- aluminum body
- brass hex nut prevents galling in the nozzle
- Viton® / Buna seals
- nylon cord retainer
- ¾" are Underwriter's Listed

Size	Part #	Price/E
¾" x ¾"	DAWS34	\$45.00
1" x 1"	DAWS10	70.25

Breakaways



Features:

- aluminum body
- brass break rings (2)
- Buna seals
- unique ball valves seal both ends when separated
- design provides consistent and reliable performance
- lightweight
- easy to repair
- ¾" are Underwriter's Listed

Size	Part #	Separation Force (Lbs)	Price/E
¾"	DAB34	325	\$68.60
1"	DAB1	325	141.00

Application:

Provides breakaway protection for high capacity fueling operations such as truck and bus terminals, mining, off-road fueling and fuel oil delivery.

Features:

- nickel plated aluminum body
- brass break rings: 4 in 1¼" and 1½"; 6 in the 2"
- Viton® / Buna seals
- check valve - PTFE ball seals both ends when separated

Size	Part #	Separation Force (Lbs)	Price/E
1¼"	DAB14	600	\$884.00
1½"	DAB15	600	884.00
2"	DAB2	800	1796.40

S