

## Cam and Groove Actuator Style Couplers

### Applications:

- suited for vapor recovery, suction pump line and other applications where it is necessary to easily drain the hose or pipe for cleaning
- can also be used when product retention in a hose or pipe is desired and damage from accidental spill from an open coupler is not a concern
- couplers work with the DBA (Dry Break Cam and Groove) popped adapters on page 92 in applications where automatic closure for the coupler is not desired

### Features:

- 316 stainless steel body
- 304 stainless steel internal components
- EZ Boss-Lock cam arms
- stainless steel locking lever standard
- available with Buna, FKM, FKM-B, EPDM, FFPM, PTFE encapsulated silicone and PTFE encapsulated FKM seals  
use with standard cam and groove dust plugs sized one size larger than the dry disconnect size
- prevents spillage from normal and accidental disconnection of the connection
- replacement parts are available, contact Dixon for more information



Female NPT	Coupler Size	Seal Material	Stainless Steel	
			Part #	Price/E
1½"	2"	Buna	<b>D2C71-150</b>	<b>\$1030.85</b>
2"	2½"		<b>D2C71-200</b>	<b>1135.10</b>
1½"	2"	FKM	<b>D2C72-150</b>	<b>1051.40</b>
2"	2½"		<b>D2C72-200</b>	<b>1156.90</b>
1½"	2"	PTFE Encapsulated Silicone	<b>D2C73-150</b>	<b>1272.75</b>
2"	2½"		<b>D2C73-200</b>	<b>1347.35</b>
1½"	2"	EPDM	<b>D2C74-150</b>	<b>1030.85</b>
2"	2½"		<b>D2C74-200</b>	<b>1135.10</b>
1½"	2"	PTFE Encapsulated FKM	<b>D2C77-150</b>	<b>1272.75</b>
2"	2½"		<b>D2C77-200</b>	<b>1347.35</b>
1½"	2"	FKM-B	<b>D2C79-150</b>	<b>1102.90</b>
2"	2½"		<b>D2C79-200</b>	<b>1214.60</b>