

Contact Name:	Company Name:	
Project Name:		

The	Right Con	nection	•																	
Contact Name:		Ball Valve Check List Company Name:																		
Date: Phone:				ione:				Ema	Email:											
Custor	ner ID	#:																		
							F	Process	Back	ground										
Proces	s Tem	ıp:							Р	lant Air S	Supply	/ (PSI):							
Produc									_		,	•	′ _							
Troduc	Jt.	_							Size											
1/4"	T	3/8"		1/2"	3/4"		1"	1-1/		1-1/2"	1	2"		2-1/2"		3"		4"	T	
., .		0.0			- Indus	trial		,		,_			at Ma			arv				
Seat Material - Industrial Seat Material - Sanitary 15% Glass Reinforced PTFE Virgin PTFE													\top							
	25% Carbon Reinforced PTFE									15% Glass Reinforced PTFE										
50% SS Reinforced PTFE									25% Carbon Reinforced PTFE											
			U	IHMW						50% SS Reinforced PTFE										
										UHMW										
					Industr	ial				Connection Sanitary										
				NPT									Clar	-						
				ket Wel									We	ld						
			150	# Flang)				0	ther:										
			Body					Flow		trol					Po	rts/Ba				
Industrial 2 piece body ndustrial 3 piece body								0° V-port					-way			3-way T				
ı	naustr	ai 3 p	olece bo	oay			W	ith 60° V					3-wa	y L		4-	way			
	Man	ual		I	Dr	neuma	atio	AC	uatio		ctric				Dood	man l	londle			
	IVIan	uai			PI	leuma	alic	On	eratio		CUIC				Dead	manr	Handle	;		
		Spri	ina retu	rn norm	ally one	า		Ор	erauc	ווע			ouble	acting						
Spring return normally open Spring return normally closed										Double acting Standard Electric										
		Opin	ig rotai		any 0.000			De	totio			0.0	aare	2 210001						
			an° (2 nositi	n)			K	tatio	П		18	∩° (2 i	nocition	1					
90° (2 position) 180° (3 position)								180° (2 position) Modulating												
Other:			100	(o poor	011)					If '	3-11/21/	way valve specify flow path. See page 166								
							D	4! - A				vaive	о орск	ony nov	patiti	. 000	page	100		
		Enal	001180	Motorio			Pne	umatic A								imais C	Switch			
Enclosure Material Aluminum Ni Plated AL NEMA						NEMA			Intrinsically Safe				Mecha		iiiii s	_	vitch			
SS Techno-polymer					NEMA			intrinoidally dure				Prox # po								
													Other:							
			Solonoi	id					Positi	ioner					Oth	or O	ntions			
12VD	Solenoid OC 220VAC Pneumatic							Electro-pneumatic						Other Options Decluchable Gear Over-Ride						
24VD				gle Coil			edback				No						Switc			
24VA																				
110VA	AC		Close	d Cente	rs		0 11.10													
							Ele	ctric Ac	tuato	r Option	าร									
Enclosure Manual Over-Ride Switches																				
NEMA 4/4X Yes								Standard Potentiometer												
NEMA 7/9 No						2 Extra Current Position							on							
	Intrins			!			Handw		41.	(D - 111		ue Sv	vitche	S		_				
12 \/5		Pov	ver Su		1		1 5 \/	wodula	ting ((Position				Decluch			Over 5			
12 VD 24VD				/AC 1PH /AC 3PH			1-5 V -20 mA		-	2-10 V	,				nable o ocal C			riue		
24VA				AC 3PI			edback		-		No				attery					
110 V			-1-1 0 V	, 10 01 1			Othe				. 40			Other	-		. Op			
77			l				Oute							Culei	, voqui	ooio.				