

British Instantaneous Fittings from Dixon Fire

The Right Connection®

Features:

- polished brass finish
- meets BS336 specifications

Adapters

Configuration		Dort #	Waight
Female	Female	Part #	Weight
21/2" BRIT	21/2" NST (NH)	BID250F	
21/2" BRIT	2½" NPSH	BID250S	3 lbs. 10 ozs.
21/2" BRIT	2½" NPT	BID250T	3 108. 10 028.
21/2" BRIT	21⁄2" BSP	BID250B	



British Instantaneous female x female threads

Configuration	Part #	Weight	
Female	Male	i ait#	vveignt
21/2" BRIT	2½" NST (NH)	BIB250F	
21/2" BRIT	2½" NPSH	BIB250S	3 lbs. 5 ozs.
21/2" BRIT	2½" NPT	BIB250T	3 108. 5 028.
21/2" BRIT	2½" BSP	BIB250B	



British Instantaneous female x male threads

Configuration		Part #	Woight	
	Male	Female	Part #	Weight
Ī	21/2" BRIT	21/2" NST (NH)	BIA250F	
	21/2" BRIT	2½" NPSH	BIA250S	2 lbs. 9 ozs.
	21/2" BRIT	2½" NPT	BIA250T	2 105. 9 025.
	21/2" BRIT	2½" BSP	BIA250B	



British Instantaneous male x female threads

Configuration		Part #	Weight
Male	Male	i dit#	vveignt
2½" BRIT	21/2" NST (NH)	BIF250F	
2½" BRIT	2½" NPSH	BIF250S	2 lbs. 5 ozs.
2½" BRIT	2½" NPT	BIF250T	2 105. 5 025.
21/2" BRIT	21/2" BSP	BIF250B	



British Instantaneous male x male threads

Plug

Size	Part #	Weight
21/2"	BIDP250	1 lb. 13 ozs.



Cap Size Part # Weight BIDC250 3 lbs. 8 ozs.



Hose Shanks

Configuration	Part #	Weight
21/2" MBI x 11/2" hose shank	BIE150	2 lbs. 11 ozs.
21/2" FBI x 11/2" hose shank	BIC150	3 lbs. 12 ozs.





BIE150

Dixon Fire

800 High Street • Chestertown, MD 21620 dixonvalve.com

ph: 877.712.6179 fx: 800.283.4966

ph: 410.778.2008

fx: 410.778.4702