



Omega™ Monitor

Features:

- brass construction
- cast-in turning vanes for a more efficient flow
- 360° horizontal and 150° vertical travel
- friction loss: 10 PSI at 800 GPM (.7 bar at 3030 LPM)
- 4 bolt hole pattern on flange
- Factory Mutual approved

Size	Inlet	Outlet	Waterway	Flow	Weight	Aluminum	
						Part #	Price/E
17" x 11½"	3" flange	2½" MNST	3"	1250 GPM	72 lbs.	AK3526-300FL	\$5400.00



Features:

- fixed teeth
- combination Straight, Stream and Fog - no shutoff
- fixed gallonage master stream nozzle
- factory set at 500 GPM (1900 lpm) can be changed in the field to 300 or 700 GPM (1140 or 2660 LPM)
- maximum operating pressure: **100 PSI** (water only)

Size	Thread	90° Spray GPM @ 100 PSI	Weight	Brass	
				Part #	Price/E
2½"	NST (NH)	NST (NH)	10 lbs.	AK4450NST	\$6262.00



Steel FirePro™ Monitor

Features:

- seamless 2½" monitor - rated at 750 GPM
- carbon steel construction, stainless steel discharge tip and ball bearings
- 360° horizontal and 140° vertical travel
- red epoxy finish standard
- 150# ASA raised face 4" flange
- FM approved

Size	Inlet Configuration	Outlet	Waterway	Flow	Weight	Carbon Steel	
						Part #	Price/E
22" x 13"	4" flange	2½" male NST	2½"	750 GPM	50 lbs.	FP475S	\$3400.00



Master Stream Nozzles

Features:

- factory set at 500 GPM
- featuring a straight stream to fog 'quick throw' pattern change
- constant gallonage
- FM approved

Size	Thread	Material	Weight	Part #	Price/E
2½"	NST (NH)	brass	19 lbs.	FP500B	\$2470.00
2½"	NST (NH)	aluminum	3 lbs.	FP500A	2055.00

P

Street Cleaning Nozzles

Feature:

- welded fabrication



Size	Connection	Aluminum		Wt. Lbs.
		Part #	Price/E	
2"	female cam	200DBAL	\$231.00	6.50
3"	female cam	300DBAL	238.00	6.75

Street Cleaning Nozzles

Features:

- delivers a flat, centered spray pattern for flushing or street cleaning apparatus
- length: 6¾", width: 8½"
- maximum operating pressure: **100 PSI** (water only)
- flows 300 GPM @ 100 PSI



Thread	Spray Direction	Brass Part #	Wt. in Lbs.	Price/E
2½" NPSH	center	BFSCN250C	8.5	\$1266.55
2½" NPSH	left	BFSCN250L	8.5	1266.55
2½" NPSH	right	BFSCN250R	8.5	1266.55