

HOW TO ORDER/NOMENCLATURE

Eccentric Collar Ball Bearings

LFT = 2 bolt light duty flange NSTU = Narrow slot take-up P2B = 2 bolt base pillow block

TB = Tapped base pillow block TP = Top angle take-up WSTU = Wide slot take-up

SCHB = Screw conveyor hanger bearing

Nomenclature

```
P2B -
                   104
      SXR -
                               NL
                                     Modification or feature
                                           E = Expansion
                                           FF = DualGuard Plus seals (with Flingers)
                                           HT = High Temperature option (400° F maximum)
                                           LL = Low torque labyrinth seal
                                            MOD = Modified
                                           NL = No Lube (sealed for life)
                                           RL = Relube (used with SLX flanges)
                         Shaft size
                               Inches:
                                     First digit = Number of inches
                                     Second & third digits = Number of sixteenths of an inch
                                            104 = Indicates 1-4/16 or 1-1/4
                                     S = Next smaller ring size. E.g. 1-1/4 206 would be written as 104S
                                     L = Next larger ring size. E.g. 1/2 204 would be written as 008L
                               Metric:
                                     First two digits = number of millimeters
                                     M = Metric
            Bearing type:
                  SXR = Wide inner ring, normal duty, Eccentric locking Collar
                  Suffixes to the above:
                         B = Low backing height pillow block
                         H = High backing height (used with non-expansion and expansion units)
                         U = Higher back pillow block (for interchangeability with competitor pillow blocks)
Housing:
      CYL = Cylindrical Unit
      F2B = 2 bolt flange
      F2BZ = 2 bolt flange with pilot machined on the back side
      F3B = 3 bolt flange
      F4B = 4 bolt flange
      FB = Flange bracket
      FC = Flanged cartridge (piloted flange)
      F&B = Fan and blower pillow block
      HNG = Hanger bearing
      LF = 3 bolt light duty flange
```

FEATURES/BENEFITS	EASY SELECTION	SELECTION/DIMENSIONS	ACCESSORIES
PAGE B7-3	PAGE B7-6	PAGE B7-12	PAGE B7-44