

Kellems® Wire Management Products
 Wire Rope Splicing Grips
 Splicing Grips



Features

- Galvanized steel meshes constructed in triple, double and single weave
- Rotating barrel helps eliminate twist in old rope being transferred to new rope



Ordering Information

Description	Cable Diameter Range Inches(cm)	UPC	Catalog Number
Rotating Wire Rope Grips, Triple, Double, Single Weave	3/4"- 7/8" (1.90-2.22)	783585317236	03317003

Listings


CSA Certified

Specifications

Strand	Galvanized Steel
Shoulders	Aluminum
Bushing	Steel
Lug	Steel
Tube	Steel
Swivel	Steel
Tag	Mylar

Performance

Mechanical	
Approximate Breaking Strength	12,500 (55,600)
Approximate Strength of Grip per Foot	6.50 (1.98)
Barrel Dimensions	4.25" (10.79) x 1.00" (2.54)
Working Load	(program formula 5% of Approximate Breaking Strength)



Online Resources

- Customer Use Drawing
- eCatalog
- Installation Instructions

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

