H-MOSS® Controls Passive Infrared Wall Mount Sensors

HUBBELL

Features

- Passive infrared, low voltage sensor for aisle and high bay applications, with photocell and isolated relay
- Coverage 120 linear ft.
- Adaptive technology "Install and forget" operation
- Narrow coverage pattern specifically for aisles and hallways
- Swivel mounting bracket included for wall or ceiling mounting

Ordering Information

Description Device Color UPC Number Catalog Number 783585349251 ATP120HBRP aisle and high bay applications, with photocell and isolated relay

Listings

cULus listed to UL 244A CEC Title 24 compliant ASHRAE 90.1 compliant

Specifications

Housing Flame retardant UL 94 V-0 ABS
Lens Polyethylene
Dimensions 6"H x 2"W x 1.5"D
Mounting Height 8 to 30 feet

Performance

Controls

Ambient Light 1 to 1000 foot candles Sensitivity Adaptive 0 to 100%

Time Delay Test (8 seconds), adaptive 8 to 40 minutes

Electrical

Isolated Relay Normally open and normally closed, terminals available

Power Requirements 24V DC nominal, 33mA from Hubbell CU series control unit

Environmental

Operating Temperature 32°F to 104°F (0°C to 40°C) with rate of change not

exceeding 20°F (11°C) per hour

Storage Temperature -20°F to 150°F (-29°C to 65°C); 0% to 95%


non-condensing relative humidity


Sensing Indicators

Passive Infrared Red LED









Complementary Products

CU300A	Control Unit Manual-ON
CU300M	Control Unit, HD, Latching, Auto/Manual-ON
CU300HD	Wall Switch Wire Guard

Online Resources

Customer Use Drawing eCatalog Installation Instructions

