

Mini-Quick® Control Connectors Field Attachable Connectors - Screw Terminal Style



	Body	Cable Range	3 Pole	4 Pole	5 Pole
Female	Straight	.24"-.32" (6.1-8.1)	HCMS03F9	HCMS04F9	HCMS05F9
		.39"-.47" (9.9-11.9)	HCMS03F13	HCMS04F13	HCMS05F13
		.47"-.55" (11.9-13.1)	—	HCMS04F16	HCMS05F16
	Right Angle	.24"-.32" (6.1-8.1)	HCMA03F9	HCMA04F9	HCMA05F9
Male In-Line	Straight	.24"-.32" (6.1-8.1)	HIMS03F9	HIMS04F9	HIMS05F9
		.39"-.47" (9.9-11.9)	HIMS03F13	HIMS04F13	HIMS05F13
		.47"-.55" (11.9-13.1)	—	HIMS04F16	HIMS05F16
	Right Angle	.24"-.32" (6.1-8.1)	HIMA03F9	HIMA04F9	HIMA05F9
Male	Straight	.24"-.32" (6.1-8.1)	HPMS03F9	HPMS04F9	HPMS05F9
		.39"-.47" (9.9-11.9)	HPMS03F13	HPMS04F13	HPMS05F13
		.47"-.55" (11.9-13.1)	—	HPMS04F16	HPMS05F16
	Right Angle	.24"-.32" (6.1-8.1)	HPMA03F9	HPMA04F9	HPMA05F9

Electrical Specifications

Voltage Rating	250V
Amperage	3 Pin - 12A 4,5 Pin - 9A
Wire Size, Max	16AWG

Mechanical Specifications

Coupling Nut	Anodized aluminum
Connector Shell	PBT
Connector Insert	PUR/PA
Contacts	Brass, Gold plate over palladium nickel

Environmental Specifications

Moisture Resistance	IP67
Operating Temperature	-40°C to 85°C

Female, Right Angle Male, Right Angle



Female, Straight Male, Straight



Male In-Line, Right Angle



Male In-Line, Straight

