

Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light and Alarm, 20A 125V, 5-20R, Ivory

By Hubbell Wiring Device-Kellems Catalog # HBL5362ISA

Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light and Alarm, 20A 125V, 5-20R, Ivory



Application

Decorator Duplex with Light and Alarm

General

Color Ivory **Environmental Conditions** Indoor Dry Unless Protected By Additional Means Indicator(s) Type LED and Audible Alarm Item Type Material Composite Material - Mounting Hardware Mounting Screws Hubbell Wiring Device-**OEM Brand Name** Operating Temperature 32 Deg F to 140 Deg F (0 Deg C to 60 Deg C) Outlet Straight Blade • Electrical - Protection

Performance

Surge Protection Receptacles

Modes - Normal and Common Modes

• Electrical - Response Time - Approximately 5 ns

• Electrical - Transient Suppression - Peak Energy (10 X 100 μ s), Peak Current $(8 \times 20 \mu s)$

Electrical - Voltage - 120V AC + 10% - 15%

• Environmental -Flammability - UL 94V-2

Environmental - Operating Temperature - 32°F to 140°F (0°C to 60°C)

Response Time

Series Specification Grade

Duplex Type

UPC 783585060279

Dimensions

Display Size Standard

Electrical Ratings

20 A Amperage Rating

Connectivity Terminal Screws

Current / Amperage Rating 20 A **Current Rating** 20 A 60 Hz Frequency Rating Phase Single Phase

Voltage Rating 125 V Voltage Rating Description 125 V

Certifications and Compliance

Industry Standard(s) • CSA Certified to

Specification C22.2 No. 42

• Listed to UL Standards 498

• UL Listed File E2186

5-20R Nema Rating

Logistics

Carton Quantity 10

Product Assets

Catalog Page - Wiring N-13 Catalog page Catalogs - Wiring Full Catalog

Engineering Drawing - HBL5362ISA AutoCAD Drawing Installation Manuals - WIRING PD1152 INSTALLINST Literature - SpikeShield® Power Quality Surge Protective Devices

Sales Drawings - WDK HBL5362 DRAWING PDF Warranty - Industrial & Commercial Products

WOR TIBESSOZION OF ENTIRE V SYZOZIO