

TVSS Duplex Receptacle with Light and Alarm, 20A 125V, 5-20R, Office White

By Hubbell Wiring Device-Kellems Catalog # HBL5362OWSA

TVSS Duplex Receptacle with Light and Alarm, 20A 125V, 5-20R, Office White



Application

Decorator Duplex with Light and Alarm

General

Color

Environmental Conditions

Indicator(s) Type
Item Type
Material
Material - Mounting Hardware
OFM Brand Name

Operating Temperature

Outlet Performance Office White

By Additional Means LED and Audible Alarm Surge Protection Receptacles Composite

Indoor Dry Unless Protected

Mounting Screws Hubbell Wiring Device-

Kellems 32 Deg F to 140 Deg F (O Deg C to 60 Deg C)

Straight Blade

 Electrical - Protection Modes - Normal and Common Modes

- Electrical Response Time
 Approximately 5 ns
- Electrical Transient
 Suppression Peak Energy
 (10 X 100 μs), Peak Current
 (8 X 20 μs)
- Electrical Voltage 120V AC + 10% - 15%
- Environmental -Flammability - UL 94V-2
- Environmental Operating Temperature - 32°F to 140°F (0°C to 60°C)

Response Time

Series Specification Grade

Type Duplex

UPC 783585060293

Dimensions

Display Size Standard

Electrical Ratings

Amperage Rating 20 A

Connectivity Terminal Screws

Current / Amperage Rating20 ACurrent Rating20 AFrequency Rating60 HzPhaseSingle Phase

Voltage Rating 125 V Voltage Rating Description 125 V

Certifications and Compliance

Industry Standard(s) • CSA Certified to

Specification C22.2 No. 42

• Listed to UL Standards 498

• UL Listed File E2186

Nema Rating 5-20R

Logistics

Carton Quantity 10

Product Assets

Catalog Page - Wiring N-13 Catalog page Catalogs - Wiring Full Catalog

Engineering Drawing - HBL5362OWSA AutoCAD Drawing Installation Manuals - WIRING_PD1152_INSTALLINST Literature - SpikeShield® Power Quality Surge Protective Devices

Sales Drawings - WDK_HBL5362_DRAWING_PDF Warranty - Industrial & Commercial Products