



Adapter, Marine, Molded Straight, Yellow

By Hubbell Wiring Device-Kellems
Catalog # [HBL61CM72](#)



Marine Adapter Molded Straight Blade

Application

Straight Adapter

General

Color	Yellow
Insulation	Insulated Body
Item Type	Adapters
Material	Composite
Number Of Pins	Male- 50A 125/250V Twist-Lock®
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	Max Continuous- 75 Degrees C, Minimum- -40 Without Impact
Performance	Environmental - Moisture Resistance - IP55 Suitability
Receptacle Type	Female- 50A 125V Twist-Lock®
UPC	783585808697

Electrical Ratings

Amperage Rating	50 A
Current / Amperage Rating	50 A
Current Rating	50 A
Voltage Rating	125/250 VAC
Wattage	12500

Product Assets

[Catalog Page - Wiring_Catalog_BB29_CatPage](#)
[Catalogs - Wiring Full Catalog](#)
[Installation Manuals - WIRING_PD2030_INSTALLINST](#)
[Literature - Hubbell Marine Full Line Catalog](#)
[Warranty - Industrial & Commercial Products](#)

Related Products

[HBL61CM56 - Adapter, Marine, Molded, Straight Blade, Yellow, 30A 125V 2-Pole 3-Wire Grounding Female to 50A 125V, 2-Pole 3- Wire Grounding Locking Male, Yellow](#)
[HBL63CM69 - Locking Devices, Twist-Lock®, Marine Grade, Receptacle, 50A 125/250V, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Galvanized](#)
[HBL61CM54 - Adapter, Marine, Molded, Straight Blade, Yellow](#)
[HBL61CM53 - Locking Devices, Twist-Lock®, Marine Grade, Ship to Shore Cables, 50A 125V, 2-Pole 3-Wire Grounding, Non-NEMA, Yellow](#)



A proud member of the Hubbell Family.