## Dixon<sup>™</sup> Type C Couplers

## female coupler x hose shank

## Features:

- Finger rings are not supplied on ½" 1" Dixon™ couplings. ½" Dixon coupler has only one cam arm.
- Couplers are supplied standard with a Buna-N gasket. Other gasket types are available on pages 78-79.







356T6 aluminum

aluminum hard coat

brass

Size	356T6 Aluminum		Aluminum Hard Coat		Brass	
	Part #	Price/E	Part #	Price/E	Part #	Price/E
1/2"	50-C-AL	\$21.50			50-C-BR	\$46.40
3/4"	75-C-AL	24.70			75-C-BR	50.95
1"	100-C-AL	27.30			100-C-BR	62.05
11/4"	125-C-AL	57.00			125-C-BR	88.00
1½"	150-C-AL	34.75	150-C-ALH	\$46.00	150-C-BR	83.60
2"	200-C-AL	37.95	200-C-ALH	57.30	200-C-BR	105.90
21/2"	250-C-AL	69.65			250-C-BR	136.00
3"	300-C-AL	60.00	300-C-ALH	87.95	300-C-BR	189.00
4"	400-C-AL	81.60	400-C-ALH	111.40	400-C-BR	238.00
5"	500-C-AL	123.85				
6"	600-C-AL	195.95	600-C-ALH	251.00	600-C-BR	814.90
8"	800-C-AL 1	757.00				



Dixon<sup>TM</sup> and Boss-Lock<sup>TM</sup> cam and groove couplings do not interchange in the  $\frac{1}{2}$ " and 8" sizes. The 8" Dixon™ design has 4 cam arms, Boss-Lock™ design has 2 cam arms.







316 stainless

Ciro	Unplated Malleable II	ron	316 Stainless Steel		
Size	Part #	Price/E	Part #	Price/E	
1/2"			50-C-SS	\$57.60	
3/4"			75-C-SS	69.10	
1"			100-C-SS	79.30	
11/4"			125-C-SS	138.40	
1½"	150-C-MI	\$51.55	150-C-SS	96.60	
2"	200-C-MI	54.00	200-C-SS	114.25	
21/2"			250-C-SS	292.50	
3"	<b>300-C-MI</b> <sup>1, 2</sup>	87.00	300-C-SS	198.70	
4"	<b>400-C-MI</b> <sup>1, 2</sup>	112.20	400-C-SS	336.00	
5"			500-C-SS	474.00	
6"	600-C-MI 1, 2	210.00	600-C-SS	548.00	

<sup>&</sup>lt;sup>1</sup> Suitable for use with King Crimp™ sleeves and ferrules, see pages 14-17.

ductile iron