

NOTES: UNL	ESS OT	HERW I SE	SPEC	IFIED
------------	--------	-----------	------	-------

- 1. DIMENSIONS ARE IN INCHES(MM).
 2. ALL DEVICES ARE 7A, 300VAC.
 3. ALL DEVICES ARE U.L. LISTED AND ARE NOT FOR CURRENT RUPTURE.
 4. THE "XXX" IN CATALOG NUMBER DENOTES LENGTH OF WIRE IN FEET. PH1012PE Q 1 Q IS TEN FEET LONG.

CATALOG NUMBER	NUMBER OF POLES	POSITION NUMBER	COLOR	CONDUCTOR NUMBER
PH1012PEXXX	12	1		P1
		2		P2
		3		P3
		4		P4
		5		P5
		6	BLUE	P6
		7	BLUE	P7
		8		P8
		9		P9
		10		P10
		11		Pi i
		12		P12

LINKOSITY™ IS A TRADEMARK OF LOCKHEED MARTIN

LI	ST OF PARTS		
DESCRIPTION	MATERIAL	FINISH	014
COUPLING NUT	BRASS	NICKEL	DIMENSION SHEET FOR CAT. NO.
INSULATOR, SOCKE	TNYLON	WHITE	2
RETAINERS	NYLON	WHITE	出
O-RING	RUBBER	BLACK	1
SOCKET CONTACT	L CUBBER VIIUA	GOLD OVER Pd/Ni	另
OVERMOLD	POLYURETHANE	GRAY	S
CABLE	18 AWG PVC	GRAY	8
PIN CONTACT	BRASS	GOLD OVER PO/Ni	
INSULATOR, PIN	1 NYLON	WHITE	SEE TABLE
<u> </u>		 	i iii
			·
			7
			Ó
			- D
			9
1	į		REPAIRABLE
			%
	1		
			Li
			į
			-
			NON-REPA
			- 20
		j	문
		į	RABLE
			Fin
	ĺ		×
	1		
RELEASE	D PER	第2/15/05	
- DUN 122	II GM		
SYM REVISI	ONS A	IPP DATE	
THE DECION	NID BINCION		
	ND DIMENSION		
PRODUCT SHOW	N ON THIS DRA	WING ARE	\leq
SUBJECT TO (CHANGE WITHOU	T NOTICE	1
			l
TITLE			(0)
LINKOSITY	M/F FX	TENSION -	\Box
18 AWG I	TC/PL TO	CABLE	$\left \begin{array}{c} \cdot \\ \cdot \end{array} \right $
10 /110 1			$ \setminus \rangle$
	WIRING DEV	ICE-KELLEMS	17.1
TOLERANCES UNLESS OTHERWISE SPECIFIED		NCORPORATED	
		PORT, CT	
FRACTIONS ± 1/64 DECIMALS ± .005	DR. BY GPH	APP. BY 6.11	
ANGLES ± 2°	TR. BY	SCALE NONE	
i si Etatustada — ii fiin	CHK'D BY CW.	DATE 2/15/05	
	= =		L

CODE 74545