

Reducing Cam and Groove Couplings

In reducing couplings, the cam and groove end is the first size given in the part number. (i.e., a 4030-B-AL is a 4" coupler to a 3" male NPT).

C

Type E

Feature:

- pressure rating is based on the seal of the mating part, see ratings on page 32

male adapter x hose shank

Size	356T6 Aluminum		Opt Qty	316 Stainless Steel	
	Part #	Price/E		Part #	Price/E
1½" x 1"	---	---	---	1510-E-SS	\$228.00
2" x 1½"	2015-E-AL ¹	\$180.00	---	2015-E-SS ¹	218.40
3" x 2"	---	---	---	3020-E-SS ¹	385.00
3" x 2½"	---	---	---	3025-E-SS	199.00
4" x 3"	4030-E-AL	86.80	10	4030-E-SS ¹	550.00
5" x 4"	5040-E-AL ¹	325.00	---	---	---



reducing
male adapter x hose shank

¹ parts are produced as a welded fabrication

Type F

Feature:

- pressure rating is based on the seal of the mating part, see ratings on page 32

male adapter x male NPT

Size	356T6 Aluminum		Opt Qty	316 Stainless Steel	
	Part #	Price/E		Part #	Price/E
1½" x 2"	1520-F-AL	\$45.00	---	---	---
2" x 1½"	2015-F-AL	45.30	---	2015-F-SS ¹	\$398.00
2" x 3"	2030-F-AL	69.00	---	---	---
3" x 1½"	3015-F-AL	64.60	10	3015-F-SS ¹	418.00
3" x 2"	3020-F-AL	64.25	10	3020-F-SS	410.00
3" x 4"	3040-F-AL	83.30	10	---	---
4" x 3"	4030-F-AL	88.90	10	4030-F-SS	325.00



reducing
male adapter x male NPT

¹ parts are produced as a welded fabrication

Adapters and Couplers with Straight Pipe Thread (NPSM)

Application:

- for delivery of dry goods

Features:

- cork buna gaskets are standard in threaded end replacement gasket; **400GAGFI, \$4.30**
- pressure rating is based on the seal of the mating part, see ratings on page 32

adapter x NPSM thread

Size	356T6 Aluminum	
	Part #	Price/E
4"	400-AS-AL	\$88.00


Feature:

- supplied standard with a Buna-N gasket, other gaskets available on pages 78-79

Boss-Lock coupler x NPSM thread

Size	356T6 Aluminum	
	Part #	Price/E
4"	ADS400	\$97.65

