

Turbo Nozzles

Features:

- 15° spray angle
- maximum temperature: **195°F**
- ceramic orifice




Part #	Description	Orifice	Nozzle Size	Maximum Working PSI	Price/E
AL-TPR25-30	¼" female inlet, dk. green	1.30 mm	4.0	3,625	\$186.00
AL-TPR25-50	¼" female inlet, purple	1.50 mm	5.5 - 6.0	3,625	186.00
AL-TPR25-70	¼" female inlet, grey	1.70 mm	7.0 - 7.5	3,625	186.00
AL-TPR35-30	¼" female inlet, dk. green	1.30 mm	4.0	5,075	282.00
AL-TPR35-50	¼" female inlet, purple	1.50 mm	5.5	5,075	282.00
AL-TPR35-70	¼" female inlet, grey	1.70 mm	6.5	5,075	282.00

Nozzle Holders

H



AL414



AL416

Feature:

- maximum temperature: **300°F**

Part #	Description	Flow (GPM)	Working PSI	Price/E
AL414	adjustable hi/low nozzle holder with nozzle protector, ¼" female inlet and outlet	7.8	3,650	\$47.25
AL416	change over nozzle, ¼" female inlet, 2 each ¼" female outlet	8	2,900	64.50

Inlet Filter for Turbo Nozzles


Features:

- ¼" female inlet, ¼" male outlet
- maximum temperature: **212°F**
- 100 mesh filter

Part #	Description	GPM	Working PSI	Price/E
AR3500	stainless steel, inlet water filter	8	5,000	\$38.20

Braided Rubber Hose



Part #	Pressure Rating (PSI)	Length	ID	Male Swivel Inlet	Male Swivel Outlet	Price/E
AR503830SSP	4,000	50'	¾"	¾"	¾"	\$242.65

Hand Crank Hose Reel


Features:

- working PSI: **3,000 PSI**
- maximum temperature: **160°F**
- ⅜" outlet, ⅜" inlet
- includes jumper hose, mounting bracket and crank handle
- steel
- holds 100' of ⅜" pressure hose

Part #	Price/E
AR-REEL100	\$406.00