




Backflow Preventer



Features:

- provides maximum protection against backflow caused by back-pressure or back-siphonage from a cross-connection wherein a contaminant hazard exists
- consists of two spring-loaded poppet type check valves and a mechanically independent, hydraulically dependent pressure differential relief valve
- three top mounted test cocks ensure easy access during repair and maintenance
- working pressure: to **175 PSIG**
- temperature range: **33°F to 180°F**
- meets Foundation for Cross Connection Control and Hydraulic Research at University of Southern California Manual Section 10, ASSE 1015, AWWA C-510 and CSA B64.4 specifications
- Underwriters Listed and Factory Mutual approved
- create a Fire Hydrant Backflow Preventer by using the **RSMSA25F20T** (page 599) and the **DMH2025F** (page 582)

| NPT Thread | Brass Part # | Price/E |
|------------|---------------|------------------|
| 2" | BFP200 | \$1793.75 |

Hand Hydrotest Pump



Features:

- designed for use in testing pipe lines, pressure tanks and pressure vessels
- uses check valves which are more efficient and longer lasting than old poppet system
- cylinder displacement: 1.37 cu. in.
- 0 -1000 PSI pressure gauge, 10' high pressure hose and quick disconnect coupler included
- piston: 7/8" with 2" stroke
- stainless steel piston
- working pressure: **1000 PSI** at 70°F (21°C)

| NPT Inlet | NPT Outlet | Aluminum Part # | Price/E |
|-----------|------------|-----------------|------------------|
| 1/2" | 1/2" | HHTP | \$2233.60 |

Large Diameter Hose Roller

P



Features:

- ABS rollers
- two man operation

| Steel Part # | Price/E |
|--------------|-----------------|
| FHR | \$606.90 |