



N412603812CDSSA

by Wiegmann
Catalog ID: N412603812CDSSA

N412 Single Door Flanged Disconnect Ultimate Series 60X38X12 316 Stainless Steel

- Bodies and doors are fabricated from 316L stainless steel
- Seams are continuously welded and ground smooth
- Doors are sealed with a poured in place gasket
- Mounting holes are located in the back of the enclosure
- Latching system interlocks with the disconnect handle for added safety

Bodies and doors fabricated from 14 gauge 316 stainless steel. Continuously plasma welded seams. Increased tub opening for better access. Concealed hinges. Easy to remove doors are interchangeable. Grounding provisions included. Doors are sealed with poured-in-place polyurethane gasket. Mounting holes in rear of enclosure. Studs for mounting optional sub panel. Door latching system installed on door with a slotted insert defeater mechanism to open. Latching system interlocks with the disconnect handle for added safety. 3pt latch system.

Product Details

General

| | |
|-------------------------|--|
| Application | These general purpose disconnect enclosures accept major brand disconnect switches and circuit breakers, available with or without Wiegmann-supplied defeater door handle and handle hardware. |
| Construction | Continuously Welded Seams |
| Finish Type | Smooth Grained |
| Latches Type | 3-Point |
| Listings | UL, CSA |
| Material | 316 Stainless Steel |
| Mounting Method | Mounting Holes |
| Number of Doors (Fixed) | 1 |
| Type | Enclosure |

| | |
|-----|--------------|
| UPC | 786725869596 |
|-----|--------------|

Dimensions

| | |
|----------------|-------------|
| Cubic Capacity | 27360 cu.in |
| Depth | 12 in |
| Height | 60 in |
| Weight | 220 lb |
| Width | 38 in |

Certifications and Compliance

| | |
|------------------|--|
| Certified Listed | <ul style="list-style-type: none">• CSA• IEC• UL |
| Nema Rating | 4 |
| UL Listed | Yes |