



PBGX9

by Wiegmann
Catalog ID: PBGX9

N12 22.5 MM 9 Pushbutton Enclosure 8.5X6.5X4.2 Carbon Steel - Gray

- Fabricated from 14 gauge steel. Continuously welded seams ground smooth. Closed cell oil resistant neoprene gasket. External mounting plates, top and bottom of enclosure. Captivated cover screws thread into sealed wells. Standard "4-way" miniature pushbutton holes accept all standard brands of miniature push buttons, switches, and pilot lights. Enclosures have internal detachable hinges to hold cover open during wiring, yet permit quick removal. Grounding provisions provided.

Product Details

General

| | |
|-----------------|--|
| Application | Designed to hold all standard brands of miniature oil-tight pushbuttons, switches, and pilot lights. Provide protection from dust, dirt, oil, and water. |
| Color | Gray |
| Construction | Continuously Welded Seams |
| Cover Type | Pushbutton;Screw |
| Finish Type | Polyester Powder |
| Listings | UL, CSA |
| Material | Carbon Steel |
| Mounting Method | External Mounting Plates |
| Mounting Type | Wall Mount |
| Number of Holes | 9 |
| Series | PBGX |
| Type | Miniature Pushbutton Enclosure |
| UPC | 786725431939 |

Dimensions

| | |
|---------------|----------|
| Actual Depth | 4.25 in |
| Actual Height | 8.500 in |
| Actual Width | 6.500 in |
| Depth | 4 in |

| | |
|--------|------|
| Height | 9 in |
| Weight | 6 lb |
| Width | 7 in |

Certifications and Compliance

| | |
|------------------|--|
| Certified Listed | <ul style="list-style-type: none">• UL• CSA |
| Nema Rating | 12 |
| UL Listed | Yes |