BRYANT®

TradeSelect, Straight Blade, Single Receptacle, Weather and Tamper Resistant, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Ivory

By Bryant Catalog # RR201IWRTR

TradeSelect, Straight Blade, Single Receptacle, Weather and Tamper Resistant, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Ivory

Features

- Tamper-resistant shutter and weather-resistance complies with national eletrical code requirements
- Smooth indented face appearance
- Multiple-drive Slot/Phillips/Robertson head screws
- Tough thermoplastic cover and base

Application

Residential Receptacles

General

Color

Ivory

Ivoire

Environmental Conditions

Item Type Material

Material - Mounting Hardware

Number Of Poles

Performance

Weather Resistant

Single

Thermoplastic Screw Mounting

2-Pole

- Electrical Current Interrupting - Certified for current interrupting at full rated current
- Electrical Dielectric Voltage - Withstands 2.000V minimum
- Environmental -Flammability - UL 94 V-1
- Environmental Operating temperature - -20°C to 60°C, without impact
- Mechanical Product Identification - Ratings are a permanent part of the device
- Mechanical Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only
- Mechanical Terminal Identification - Terminals identified in accordance with UL 498 and CSA C22.2, No. 41



Dimensions

Display Size Standard Sized Product

Electrical Ratings

Amperage Rating 20 A
Connectivity Side Wired
Current / Amperage Rating 20 A
Current Rating 20 A
Phase Single Phase

Voltage Rating125 VACVoltage Rating Description125 VACWattage2500

Conductor Related

Number Of Wires 3-Wire Grounding
Wire Size #12 AWG to #10 AWG

Certifications and Compliance

Industry Standard(s)

- Certified to CSA, C22.2, No. 41 File No. 23253
- NEMA® WD-6 Compliant
- UL Listed to UL498 File No. F2185

Nema Rating 5-20R

Logistics

Carton Quantity 10

Product Assets

Catalog Page - Bryant A-19 Catalog page Catalogs - Bryant Full Line Catalog Literature - Residential Catalog

UPC 883778302961

