



TradeSelect, Straight Blade, Single Receptacle, Weather and Tamper Resistant, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Ivory

By Hubbell Wiring Device-Kellems
Catalog # [RR201IWRTR](#)

TradeSelect, Straight Blade, Single Receptacle, Weather and Tamper Resistant, 20A 125V, 2-Pole 3-Wire Grounding, 5-20R, Ivory

Features

- Tamper-resistant shutter and weather-resistance complies with national electrical code requirements
- Smooth indented face appearance
- Multiple-drive Slot/Phillips/Robertson head screws
- Tough thermoplastic cover and base

Application

Residential Receptacles

General

Color	<ul style="list-style-type: none">• Ivory• Ivoire
Environmental Conditions	Weather Resistant
Item Type	Single
Material	Thermoplastic
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
OEM Brand Name	Hubbell Wiring Device-Kellems
Performance	<ul style="list-style-type: none">• Electrical - Current Interrupting - Certified for current interrupting at full rated current• Electrical - Dielectric Voltage - Withstands 2,000V minimum• Environmental - Flammability - UL 94 V-1• Environmental - Operating temperature - -20°C to 60°C, without impact• Mechanical - Product Identification - Ratings are a permanent part of the device• Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only• Mechanical - Terminal Identification - Terminals



Electrical Ratings

Amperage Rating	20 A
Connectivity	Side Wired
Current / Amperage Rating	20 A
Current Rating	20 A
Phase	Single Phase
Voltage Rating	125 VAC
Voltage Rating Description	125 VAC
Wattage	2500

Conductor Related

Number Of Wires	3-Wire Grounding
Wire Size	#12 AWG to #10 AWG

Certifications and Compliance

Industry Standard(s)	<ul style="list-style-type: none">• Certified to CSA, C22.2, No. 41 File No. 23253• NEMA® WD-6 Compliant• UL Listed to UL498 File No. E2185
----------------------	---

Nema Rating	5-20R
-------------	-------

Logistics

Carton Quantity	10
-----------------	----

Product Assets

[Catalog Page - Wiring AA-17](#) [Catalog Page Catalogs - Wiring Full Catalog](#)
[Engineering Drawing - RR201IWRTR AutoCAD Drawing](#)
[Installation Manuals - WIRING_PD2131_INSTALLINST](#)
[Literature - Residential Product Guide](#)
[Literature - Residential Catalog](#)
[Sales Drawings - WDK_RR201IWRTR_DRAWING_PDF](#)
[Warranty - tradeSELECT™ and netSELECT®](#)
[Video - Tradeselect Devices](#)
[Video - Tamper-Resistant Receptacles](#)

Related Products

[RR205I - TradeSelect, Straight Blade Devices, Residential Grade, Receptacles, Single, 20A 250V, 2-Pole 3-Wire Grounding, 6-20R, Self Grounding, Ivory](#)
[RR201LAWRTR - TradeSelect, Straight Blade, Single Receptacle, Weather and Tamper Resistant, 20A 125V, 2-Pole](#)

	identified in accordance with UL 498 and CSA C22.2, No. 41	3-Wire Grounding, 5-20R, Light Almond
UPC	883778302961	RR151I - TradeSelect, Straight Blade Devices, Receptacles, Residential Grade, Single, 15A 125V, 2-Pole 3-Wire Grounding, 5-15R, Ivory
Dimensions		RR155I - TradeSelect, Straight Blade Devices, Receptacles, Residential Grade, Single, 15A 250V, 2-Pole 3-Wire Grounding, 6-15R, Ivory
Display Size	Standard Sized Product	SS7 - Wallplates and Boxes, Metallic Plates, 1- Gang, 1) 1.40" Opening, Standard Size, Stainless Steel



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
WDK-RR201IWRTR-SPEC-EN | REV 5/2023