## Switches, Three Way 15A, 120V AC

## **Residential Toggle Switch**

# HUBBELL

#### **Features**

- Hi-visibility yellow base for easy installation
- Elongated strap for easier wall box mounting
- Tough thermoplastic with ultrasonically welded cover and base

#### **Ordering Information**

Color **UPC Number Catalog Number** Description Self-Grounding, Push & Side Brown 883778101076 **RS315S** 

#### Listings

UL Listed E3896 **CSA Certified** 

#### **Specifications**

PVC Top Material **PVC Base Material** Toggle Material Nylon Silver Alloy Contacts **Terminal Screws Brass** Auto Grounding Mounting Bridge Galvanized Steel **Ground Screw** Steel (Green) Zinc-Plated Steel

# **Performance**

Mounting Screw

**Electrical** 

Withstands 1500V AC minimum for 1 minute Dielectric Voltage

Max. Continuous Current 15A 120V AC Max. Working Voltage

Minimum 1.5 times rating Overload Temperature Rise 30°C maximum at rated current

Mechanical

#14 AWG min. - #12 AWG max. solid and **Terminal Accommodations** 

stranded copper wire only

**Environmental** 

Flammability UL 94 V-2

Operating Temperature Maximum continuous 60°C; minimum -20°C (w/o

impact)

#### **Online Resources**

eCatalog



