Combination Plates, 4- and 5-Gang

Description	Color	Nylon Standard	Nylon Mid-Size	Material	Metal Catalog Number
4-Gang, 3-Toggle, 1-Duplex	Brown Ivory Light Almond White	NP38 NP38I NP38LA NP38W	- - -	Aluminum Brass Brass Plated Chrome S/S 302/304 S/S 430	0 0 0 5\$\$\$8 -
4-Gang, 3-Toggle, 1-Decorator	Black Brown Gray Ivory Light Almond White	NP326BK NP326 NP326GY NP326I NP326LA NP326W	- - - - -	Aluminum Brass Brass Plated Chrome S/S 302/304 S/S 430	0 0 0 SS326 -
4-Gang, 2-Toggle, 2-Decorator	Black Brown Gray Ivory Light Almond White	NP2262BK NP2262 NP2262GY NP2262I NP2262LA NP2262W	- - - - - -	Aluminum Brass Brass Plated Chrome S/S 302/304 S/S 430	0 0 0 0 -
5-Gang, 4-Toggle, 1-Duplex	Brown Ivory White	NP48 NP48I NP48W	-	Aluminum Brass Brass Plated Chrome S/S 302/304 S/S 430	0 0 0 0 -

Note: All nylon wallplates feature pre-inserted captive screws for faster assembly, up to 6-gang.

DAvailable as a custom wallplate, see pages 0-31 to 0-34. Consult custom wallplates section for additional openings and combinations.

Specifications

UL Standard 514D.	
UL Standard 514D.	
UL Files #E31999,E92074.	
CSA Standard C22.2 No. 42.1.	
CSA File 1733174.	
	UL Standard 514D. UL Files #E31999,E92074. CSA Standard C22.2 No. 42.1.

Product	Thickness	Mounting Screw(s)	Appearance
Nylon Plate	.06 in. (1.5).	Steel (painted slotted screw head).	Smooth gloss finish.
302/304 Stainless Steel Plate (18% Chromium,8% Nickel)	.035 in. (0.9) nominal.	302/304 stainless steel (18% chromium, 8% nickel). Slotted screw head.	Horizontal brushed finish.
430 Stainless Steel Plate (17% Chromium, less than 0.5% Nickel)	.035 in. (0.9) nominal.	302/304 stainless steel (17% chromium, less than 0.5% nickel). Slotted screw head.	Horizontal brushed finish.
Brass Plate (70% Copper, 30% Zinc)	.04 in. (1.0).	Brass (70% Coppper,30% Zinc). Slotted screw head.	Horizontal brushed finish.
Aluminum Plate	.05 in. (1.3).	302/304 stainless steel (17% chromium, less than 0.5% nickel). Slotted screw head.	Horizontal brushed finish.
Brass Plated Steel Plate	.03 in. (0.8) nominal.	Brass slotted head.	Polished, coated to inhibit oxidation.
Chrome Plated Steel Plate	.03 in. (0.8) nominal.	302/304 stainless steel (17% chromium, less than 0.5% nickel). Slotted screw head.	Polished, coated to inhibit oxidation.
Steel Painted Plate	.03 in. (0.8) nominal.	Steel (painted slotted screw head).	Powder coat paint.

Note: All nylon plates include captive mount screws.

Nylon plates have an operating temperature of -40°C to 85°C.

Dimensions in Inches (mm)