## D

## FIOMAX ¾" Series

#### Features:

- 6 nozzle and receiver sets color coded for quick identification of mating parts; each color nozzle and receiver only couples with matching color component providing complete protection against cross contamination
- maximum flow rate: 50 GPM at 40 PSI
- working pressure rating: 200 PSI

#### **Nozzles**

Male Thread	Description	Anodized Aluminum		
	Description	Part #	Price/E	
¾" NPT	red nozzle with plug	ENBL-P	\$610.95	
	gold nozzle with plug	ENBL-P2	610.95	
	teal nozzle with plug	ENBL-P3	610.95	
	violet nozzle with plug	ENBL-P4	610.95	
	navy nozzle with plug	ENBL-P5	610.95	
	copper nozzle with plug	ENBL-P6	610.95	
	•	•		



_				
Re	ce	IV	e	rs

Male Thread	Description	Anodized Aluminum		
	Description	Part #	Price/E	
34" NPT	red receiver with cap	ERS-C	\$296.75	
	gold receiver with cap	ERS-C2	296.75	
	teal receiver with cap	ERS-C3	296.75	
	violet receiver with cap	ERS-C4	296.75	
	navy receiver with cap	ERS-C5	296.75	
	copper receiver with cap	ERS-C6	296.75	



ERS series is available with JIC bulkhead base, substitute 'J' for 'S', example: ERJ-C2

# FloMAX High Flow 1" Series

#### Features:

- 7 nozzle and receiver sets color coded for quick identification of mating parts; each color nozzle and receiver only couples with matching color component provides complete protection against cross contamination
- nozzle/receiver combination has a flow area equivalent to a 1" schedule 80 pipe
- working pressure: 500 PSI with burst pressure: 1500 PSI
- all wear parts are stainless steel providing long life and corrosion resistance
- all non-wear parts are colored anodized aircraft grade aluminum providing high strength, lightweight and corrosion resistance
- standard nozzle mounting is a 1" female NPT and for the receiver a 1" male NPT; receivers supplied with 1" female NPT threaded base
- nozzle incorporates a "ball lock" mechanism ensuring smooth and reliable operation
- nozzle length: 3.90" (99 mm)
- receiver length: 3.44" (87 mm)
- nozzle and receiver coupled length: 5.44" (138 mm)
- diameter: 2.50" (64 mm)
- hex size: 2" (51 mm)

### **Nozzles**

Female NPT	Description	Anodized Aluminum		
remale NF i	Description	Part #	Price/E	
1"	red nozzle with plug	HFN-P1	\$685.10	
	gold nozzle with plug	HFN-P2	685.10	
	teal nozzle with plug	HFN-P3	685.10	
	violet nozzle with plug	HFN-P4	685.10	
	navy nozzle with plug	HFN-P5	685.10	
	copper nozzle with plug	HFN-P6	685.10	
	blue/gray nozzle with plug	HFN-P7	685.10	



R	Δ	r	Δ	П	١,	Δ	r	C
- 11	┖	v	C	ш	v	C		J

Description	Anodized Aluminum		
Description	Part #	Price/E	
red receiver with cap	HFR-C1	\$432.00	
gold receiver with cap	HFR-C2	432.00	
teal receiver with cap	HFR-C3	432.00	
violet receiver with cap	HFR-C4	432.00	
navy receiver with cap	HFR-C5	432.00	
copper receiver with cap	HFR-C6	432.00	
blue/gray receiver with cap	HFR-C7	432.00	
	gold receiver with cap teal receiver with cap violet receiver with cap navy receiver with cap copper receiver with cap	red receiver with cap gold receiver with cap teal receiver with cap violet receiver with cap navy receiver with cap copper receiver with cap thereof hereof	

