



	ROTATION FACING LEAD END	L1	L2	JOIN	INSULATE SEPARATELY
HIGH	C.C.W.	P1	T4 T5	T2 T3,T8	P2
VOLT	C.W.	P1	T4 T8	T2 T3,T5	P2
LOW	C.C.W.	P1	T2,T4 T5	P2 T3,T8	
VOLT	C.W.	P1	T2,T4 T8	P2 T3,T5	

				TOLERANCES UNLESS OTHERWISE SPECIFIED		LE	LEESON FLECTRIC CORPOR			ORPORATION		
				DEC.	INCHES	METRIC						
05	REMOVED OPTIONAL PRESSURE CONNECTOR	ARV 2/25/08		.x	±	±	DRAWN	PG 10/27/86	TITLE	EXTERNAL WIRING DIAGRAM		
04	REVISED TO OPTIONAL PRESSURE CONNECTOR	PG 9/14/01		.xx	±	±	APPR.			TYPE "C" W/ PROTECTOR		
03	D3 UPDATED TO CURRENT STANDARDS DBT 8/13/			.xxx	±	±	R.F.P.		MAT'L.	MAT'L. DECAL - 004011		- 004011
NO.	O. REVISION BY &		CH'K'D.	.xxxx	±	±	SCALE	1=1		SOLID STATE SWITCH		TATE SWITCH
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT — DO NOT SCALE THIS PRINT				FRACT	ONS ±		REF.	PAGE 1	FINISH	KANSAS	REV.	DRAWING NO.
				ANGLE	S ±		FMF	101120		STANDARD	05	005242-02