






Regulatory Information	Additional Notes
Rexnord, TableTop and HP are trademarks of Rexnord Industries, LLC. All rights reserved.	Stocked in 160 pitch, 10 ft (3.048 m) length strands. Uses 63 carbon steel (S) base chain (Part #63-BC). Chain runs on ANSI No. 60 sprockets. Chain breakers available. For additional material information, see material portfolio.

NS63 Thermoplastic Split Sprocket




NS63 Thermoplastic Split Sprocket Information

[illegible]

Shaft-ready round bore sprockets are shipped with keyway and no setscrew. Idler bores are designed to spin freely on the shaft.


Corner Track (Two Piece)



Corner track kit supplied as one 90° inside and one 90° outside track, which can be used as either carry or return.

Corner Track Kit Number	Accommodates Top Plate Width		Nominal Corner Radius		Inside Track Radius		Outside Track Radius		Thickness		Width		Material	Color	Approximate Corner Track Kit Weight	
	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm			lbs	kg
	TAB Design															
U18R6	All	All	18.0	457	17.3	439	18.7	475	0.75	19.1	1.5	38	UHMWPE	White	2.63	1.19
U24R6	All	All	24.0	610	23.3	592	24.7	627	0.75	19.1	1.5	38	UHMWPE	White	3.51	1.59

Corner Track (Four Piece)



Corner track kit supplied as two 45° inside and two 45° outside track, which can be used as either carry or return.

Corner Track Kit Number	Accommodates Top Plate Width		Nominal Corner Radius		Inside Track Radius		Outside Track Radius		Thickness		Width		Material	Color	Approximate Corner Track Kit Weight	
	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm			lbs	kg
	TAB Design															
U30R6	All	All	30.0	762	29.3	744	30.7	780	0.75	19.1	1.5	38	UHMWPE	White	4.38	1.99