

Dixon™ Worm Gear Clamps

Features:

- clamp meets SAEJ1508 which supercedes Mil Spec WW-C-440B
- four-piece construction
- screw design: 5/16" slotted hex head
- maximum recommended torque 50 in. lbs.
- **all clamps sold 10 per box**

Style HS material:

- band and housing: SAE 201/301 series stainless
- screw: SAE 1018 case-hardened, hex-free chrome zinc-plated steel

Style HSS material:

- band and housing: SAE 300 series stainless
- screw: SAE 300 series stainless



style HSS

Band Width	Hose OD		style HS		Master Case Qty	style HSS		Master Case Qty	
	from	to	Part #	Price /Each		Part #	Price /Each		
1/2"	7/16"	25/32"	HS6	\$1.50	200	HSS6	\$2.00	200	
	1/2"	29/32"	HS8	1.50	200	HSS8	2.00	200	
	9/16"	1-1/16"	HS10	1.50	500	HSS10	2.00	500	
	11/16"	1-1/14"	HS12	1.55	500	HSS12	2.00	500	
	13/16"	1-1/2"	HS16	1.55	500	HSS16	2.00	500	
	13/16"	1-3/4"	HS20	1.55	500	HSS20	2.05	500	
	1-1/16"	2"	HS24	1.55	500	HSS24	2.05	500	
	1-5/16"	2-1/4"	HS28	1.60	500	HSS28	2.05	500	
	1-9/16"	2-1/2"	HS32	1.60	500	HSS32	2.05	500	
	1-13/16"	2-3/4"	HS36	1.65	500	HSS36	2.15	500	
	2-1/16"	3"	HS40	2.00	200	HSS40	2.45	200	
	2-5/16"	3-1/4"	HS44	2.20	200	HSS44	2.80	200	
	2-9/16"	3-1/2"	HS48	2.20	200	HSS48	2.80	200	
	2-13/16"	3-3/4"	HS52	2.40	200	HSS52	2.95	200	
	3-1/16"	4"	HS56	2.40	200	HSS56	2.95	200	
	3-5/16"	4-1/4"	HS60	2.50	200	HSS60	3.00	200	
	9/16"	3-9/16"	4-1/2"	HS64	2.50	200	HSS64	3.00	200
		1-7/8"	5"	HS72	2.70	100	HSS72	3.30	100
2-1/2"		5-1/2"	HS80	3.10	100	HSS80	3.40	100	
3-1/8"		6"	HS88	3.20	100	HSS88	3.75	100	
3-5/8"		6-1/2"	HS96	3.25	100	HSS96	3.85	100	
4-1/8"		7"	HS104	3.30	100	HSS104	3.35	100	
5-5/8"		8-1/2"	HS128	4.90	100	HSS128	5.25	100	
7-1/8"		10"	HS152	5.25	100	HSS152	5.80	100	
9-3/8"		12-1/4"	HS188	5.75	100	HSS188	6.35	100	
10-1/8"		13"	HS200	5.80	100	HSS200	6.80	100	
10-7/8"		13-3/4"	HS212	5.90	100	HSS212	7.15	100	
11-5/8"		14-1/2"	HS224	6.55	100	HSS224	7.60	100	
12-3/8"		15-1/4"	HS236	7.10	100	HSS236	8.40	100	
13-1/8"		16"	HS248	7.45	100	HSS248	9.40	100	
17-1/8"		20"	HS312	9.10	100	HSS312	10.75	100	

K

Miniature Worm Gear Clamps

Features:

- meets SAE J1508
- screw design: 1/4" slotted hex head
- maximum recommended torque 15 in. lbs.
- **all clamps sold 10 per box**

Style MH material:

- band and housing: SAE 201/301 series stainless
- screw: SAE 1018 case-hardened, hex-free chrome zinc-plated steel

Style MAH material:

- band and housing: SAE 300 series stainless
- screw: SAE 300 series stainless



style MH

Band Width	Hose OD		style MH		Master Case Qty	style MAH		Master Case Qty
	from	to	Part #	Price /Each		Part #	Price /Each	
5/16"	7/32"	5/8"	MH4	\$1.15	500	MAH4	\$1.45	500
	7/16"	25/32"	MH6	1.15	500	MAH6	1.45	500
	1/2"	29/32"	MH8	1.35	200	MAH8	1.65	200
	9/16"	1-1/16"	MH10	1.35	200	MAH10	1.65	200
	11/16"	1-1/4"	MH12	1.40	200	MAH12	1.75	200
	15/16"	1-1/2"	MH16	1.40	200	MAH16	1.75	200
	1-3/16"	1-3/4"	MH20	1.45	200	MAH20	1.75	200



Torque ratings correspond to the torque rating of the screw of the clamp and are *not* an indication of the working pressure of any hose assembly installed with this clamp.