

Swaged Cam and Groove

Applications:


- Developed specifically for chemical transport hoses having Crosslinked Polyethylene (XLPE) or Ultra High Molecular Weight Polyethylene (UHMW) tubes. Swaged Boss-Lock™ provides you with a permanently attached cam and groove fitting when superior coupling retention is required.

Features:

- in testing tank transport hoses from a wide variety of manufacturers, the swaged Boss-Lock™ fitting proved itself to be the clear winner in overall performance
- also available on special order for other sizes or hose OD's, consult the factory for pricing and availability
- special equipment required for installation*, consult Dixon™ for pricing and availability or refer to page 434 for more information

EZ Boss-Lock™ type C coupler with ferrule

Size	Hose OD		316 Stainless Steel	
	from	to	Part #	Price/E
¾"	1-6/64"	1-22/64"	RC075EZ-70	\$130.70
1"	1-29/64"	1-35/64"	RC100EZ-20	137.10
1"	1-36/64"	1-44/64"	RC100EZ-70	141.40



coupler x hose shank with ferrule

Boss-Lock™ type E adapter with ferrule

Size	Hose OD		316 Stainless Steel	
	from	to	Part #	Price/E
¾"	1-6/64"	1-22/64"	RE075-1370	\$91.50
1"	1-29/64"	1-35/64"	RE100-1620	69.00
1"	1-36/64"	1-44/64"	RE100-1770	76.30



adapter x hose shank with ferrule

Notched Ferrules

Size	Hose OD		304 Stainless Steel	
	from	to	Part #	Price/E
1½"	1-60/64"	2-12/64"	GAS2334NO	\$34.80
1½"	2-4/64"	2-22/64"	GAS2370NO	38.35
2"	2-30/64"	2-44/64"	GAS2709NO	31.80
2"	2-42/64"	2-54/64"	GAS2885NO	69.55
3"	3-30/64"	3-46/64"	GAS3760NO	45.40
3"	3-47/64"	3-54/64"	GAS3885NO	62.10
4"	4-40/64"	4-47/64"	GAS5010NO	258.75



Dixon™ stems and ferrules are specifically designed to be used together as a coupling system.

Due to differences in dimensions and tolerances for safety reasons, do not use other manufacturer's stems or ferrules with Dixon™ Holedall™ products.