

Stainless Steel Ball Valves

Full Port, Locking Handle

Application:

- for use with water, oil and gas

Features:

- pressure rating: ¼" - 2" rated to **1000 PSI** WOG (CWP)
2½" - 3" rated to **800 PSI** WOG (CWP)
100 PSI saturated steam
- 316 stainless steel body, ball and stem
- R-PTFE seat, joint gasket and thrust washer
- plastic cover on handle
- blow-out proof stem design
- temperature range: **-20°F to 450°F**
- lockable

**female NPT x female NPT**

Size	Port	316 Stainless Steel	
		Part #	Price/E
¼"	full	SSLBV25	\$43.00
⅜"	full	SSLBV38	44.00
½"	full	SSLBV50	48.00
¾"	full	SSLBV75	70.00
1"	full	SSLBV100	90.00
1¼"	full	SSLBV125	129.00
1½"	full	SSLBV150	171.00
2"	full	SSLBV200	236.00
2½"	full	SSLBV250	510.00
3"	full	SSLBV300	750.00


Reduced Port, Locking Handle

Application:

- for use with water, oil and gas

Features:

- pressure rating: **800 PSI** WOG; **100 PSI** saturated steam
- 316 stainless steel body, ball and stem
- R-PTFE seat, joint gasket and thrust washer
- plastic cover on handle
- blow-out proof stem design
- temperature range: **-20°F to 450°F**
- lockable

**female NPT x female NPT**

Size	Port	316 Stainless Steel	
		Part #	Price/E
¼"	reduced	SSLBV25SP	\$28.50
⅜"	reduced	SSLBV38SP	30.50
½"	reduced	SSLBV50SP	32.50
¾"	reduced	SSLBV75SP	44.00
1"	reduced	SSLBV100SP	63.00
1¼"	reduced	SSLBV125SP	84.00
1½"	reduced	SSLBV150SP	115.00
2"	reduced	SSLBV200SP	162.00