



## Non-rising Stem Wedge Disc Gate Valves




### Features:

- red iron handwheel, with brass cap and chain
- cap not included on the NYFD threaded valve and special threaded valves
- solid wedge disc with tapered seats
- 2½" U/L listed and FM approved
- FM approved
- working pressure: **300 PSI** at 70°F (21°C)
- not recommended for wet standpipe systems, use AV250 (18-157) for this purpose, see page 545
- other configurations are available, contact Dixon™ for additional information



Inlet Female NPT	Outlet Male Thread	U/L	Cast Brass Part #	Price
1½"	1½" NST (NH)	no	<b>WDGV150F</b>	<b>\$418.00</b>
2½"	2½" NST (NH)	yes	<b>WDGV250F</b>	<b>888.00</b>
2½"	2½" NYFD	yes	<b>WDGV250NYFD</b>	<b>888.00</b>

### Dimensions



Size	A	B	C	D
1½"	3-49/64"	5-5/8"	1-1/8"	6-3/8"
2½"	6"	10-3/4"	2-1/2"	13-1/4"



## Global Non-rising Stem Wedge Disc Gate Valves




### Features:

- working pressure: **300 PSI** (2069 kPa)
- custom male thread available
- non-rising stem
- cast brass with solid wedge disc and tapered seats
- red iron wheel handle with cap and chain (cap not supplied on non-standard threads)
- alloy = DZR brass
- furnished with 2½" NST brass cap and chain
- available finish:
  - cast (standard)
  - polished trim - P
  - cast chrome - RC
  - polished chrome trim - C

Inlet Female NPT	Outlet Male NST	U/L	Cast DZR Brass Part #	Price
2½"	2½"	no	<b>GWDGV250F</b>	<b>\$280.40</b>

### Dimensions



Size	A	B	C	D
2½"	5"	7¾"	2½"	10"