

WS Series Couplings

Application:

- used extensively in oil field and off shore oil rig applications

Feature:


- interchanges with Snap-Tite 75 series

High Pressure Couplers



| Body Size | Female NPTF | PSI at 70°F | Material | Part # | Price/E | Opt Qty |
|-----------|-------------|-------------|----------|----------------|-----------------|---------|
| 3/4" | 3/4" - 14 | 5,000 | steel | 6WSF6 | \$155.44 | 5 |
| 1" | 1" - 11½ | 5,000 | steel | 8WSF8 | 233.16 | 5 |
| 1¼" | 1¼" - 11½ | 5,000 | steel | 10WSF10 | 394.31 | 1 |
| 1½" | 1½" - 11½ | 5,000 | steel | 12WSF12 | 582.88 | 1 |
| 2" | 2" - 11½ | 5,000 | steel | 16WSF16 | 834.32 | 1 |

Plugs



| Body Size | Male NPTF | PSI at 70°F | Material | Part # | Price/E | Opt Qty |
|-----------|-----------|-------------|----------|----------------|-----------------|---------|
| 3/4" | 3/4" - 14 | 5,000 | steel | WS6F6 | \$142.86 | 5 |
| 1" | 1" - 11½ | 5,000 | steel | WS8F8 | 171.44 | 5 |
| 1¼" | 1¼" - 11½ | 5,000 | steel | WS10F10 | 314.31 | 1 |
| 1½" | 1½" - 11½ | 5,000 | steel | WS12F12 | 491.45 | 1 |
| 2" | 2" - 11½ | 5,000 | steel | WS16F16 | 800.03 | 1 |

Blowout Prevention Safety

Applications:

- designed for use in oil rig BOP systems where couplings are required to operate under fire conditions in an emergency

Features:


- fire tested and Lloyd's certified to 700°C (1300°F) in accordance with API 16D (Certificate #NAO 0601041/1)
- Sleeve is cast using a process that provides better surface finishes, tighter tolerance control, and excellent repeatability.
- Blowout Prevention Couplings are individually marked with the BOP series designation.

Couplers



| Body Size | Female NPTF | PSI at 70°F | Material | Part # | Price/E | Opt Qty |
|-----------|-------------|-------------|----------|--------------------|-----------------|---------|
| 3/4" | 3/4" - 14 | 5,000 | steel | 6WSF6-BOP | \$228.58 | 5 |
| 1" | 1" - 11½ | 5,000 | steel | 8WSF8-BOP | 320.02 | 5 |
| 1¼" | 1¼" - 11½ | 5,000 | steel | 10WSF10-BOP | 514.31 | 1 |
| 1½" | 1½" - 11½ | 5,000 | steel | 12WSF12-BOP | 731.46 | 1 |
| 2" | 2" - 11½ | 5,000 | steel | 16WSF16-BOP | 1028.62 | 1 |

Plugs



| Body Size | Male NPTF | PSI at 70°F | Material | Part # | Price/E | Opt Qty |
|-----------|-----------|-------------|----------|--------------------|-----------------|---------|
| 3/4" | 3/4" - 14 | 5,000 | steel | WS6F6-BOP | \$177.15 | 5 |
| 1" | 1" - 11½ | 5,000 | steel | WS8F8-BOP | 188.58 | 5 |
| 1¼" | 1¼" - 11½ | 5,000 | steel | WS10F10-BOP | 377.16 | 1 |
| 1½" | 1½" - 11½ | 5,000 | steel | WS12F12-BOP | 571.45 | 1 |
| 2" | 2" - 11½ | 5,000 | steel | WS16F16-BOP | 960.04 | 1 |

Dust Plugs



| Body Size | Material | Part # | Price/E | Opt Qty |
|-----------|----------|-----------------|----------------|---------|
| 3/4" | aluminum | 6WSDP-A | \$39.31 | 25 |
| 1" | aluminum | 8WSDP-A | 50.40 | 10 |
| 1¼" | aluminum | 10WSDP-A | 70.55 | 10 |
| 1½" | aluminum | 12WSDP-A | 75.59 | 5 |
| 2" | aluminum | 16WSDP-A | 125.98 | 5 |

Dust Caps



| Body Size | Material | Part # | Price/E | Opt Qty |
|-----------|----------|-----------------|----------------|---------|
| 3/4" | aluminum | WS6DC-A | \$39.31 | 25 |
| 1" | aluminum | WS8DC-A | 50.40 | 10 |
| 1¼" | aluminum | WS10DC-A | 70.55 | 10 |
| 1½" | aluminum | WS12DC-A | 75.59 | 5 |
| 2" | aluminum | WS16DC-A | 125.98 | 5 |