

## Synthetic Single Jacket Mill Hose

### Application:

- used in open end water discharge applications only, not intended for fire fighting service



### Features:

- outer construction: single jacket, all polyester
- tube construction: black, PVC rubber
- Consult Dixon™ for pricing and availability of additional lengths and other configurations.

**Coupled with NPSH female and male King™ short shank couplings, crimp sleeve, Aluminum shank with brass pin lug swivel nut**

Size	Length	Working Pressure PSI at 70°F	Part #	Price/E
1½"	25'	75	<i>M15-25KAS</i>	\$98.85
1½"	50'	75	<i>M15-50KAS</i>	159.50
2"	25'	75	<i>M20-25KAS</i>	115.00
2"	50'	75	<i>M20-50KAS</i>	179.30
2½"	25'	50	<i>M25-25KAS</i>	148.00
2½"	50'	50	<i>M25-50KAS</i>	230.30
3"	25'	50	<i>M30-25KAS</i>	203.75
3"	50'	50	<i>M30-50KAS</i>	291.10



**Coupled with NST (NH) female and male King™ short shank couplings, crimp sleeve, Aluminum shank with brass pin lug swivel nut**

Size	Length	Working Pressure PSI at 70°F	Part #	Price/E
1½"	25'	75	<i>M15-25KAF</i>	\$113.35
1½"	50'	75	<i>M15-50KAF</i>	160.35
2½"	25'	50	<i>M25-25KAF</i>	177.90
2½"	50'	50	<i>M25-50KAF</i>	254.70



**Coupled with female and male (C & E) global aluminum cam and groove, crimp sleeve**

Size	Length	Working Pressure PSI at 70°F	Part #	Price/E
1½"	25'	112	<i>M15-25GAX</i>	\$124.75
1½"	50'	112	<i>M15-50GAX</i>	185.25
2"	25'	112	<i>M20-25GAX</i>	142.35
2"	50'	112	<i>M20-50GAX</i>	199.40
2½"	25'	112	<i>M25-25GAX</i>	174.45
2½"	50'	112	<i>M25-50GAX</i>	245.75
3"	25'	112	<i>M30-25GAX</i>	217.30
3"	50'	112	<i>M30-50GAX</i>	272.30
4"	25'	112	<i>M40-25GAX</i>	275.10
4"	50'	112	<i>M40-50GAX</i>	448.35



- additional lengths and configurations are available, contact Dixon™

P