



MAXIMUM FACE RUNOUT TO BE .004 T.I.R.
MAXIMUM PILOT ECCENTRICITY TO BE .004 T.I.R.
PERMISSIBLE SHAFT RUNOUT TO BE .002 T.I.R.

MOTOR SPECIAL FEATURES
DRAIN HOLES IN FRAME (UNPLUGGED)
MANUAL RESET OVERLOAD PROTECTOR
FLINGER
GASKETS THROUGHOUT

DASH NO.	"C"	"AD"
850	13.97	4.50
900	14.47	5.00
950	14.97	5.50
1000	15.47	6.00
1050	15.97	6.50
1100	16.47	7.00
1150	16.97	7.50
1200	17.47	8.00

					TOLERANCES UNLESS SPECIFIED	 REGAL-BELOIT CORPORATION	DRAWN	LST 2/27/04	
				DEC	INCHES		CHK	RW 2/27/04	
				X	±.1		APPR	KH 2/27/04	
				XX	±.03			SCALE	1:2
				XXX	±.005			REF	
-	UPDATED & REDRAWN IN SOLIDWORKS	LST 11/12/2009	XX	XXXX	±.0005		MATL FARM DUTY	FMF	
NO	REVISION	BY & DATE	CHK	ANG	±1/2°	FINISH	PAGE	OF	
<div>THIRD ANGLE PROJECTION</div> 			RFP	PREV			SIZE	DRAWING NO	REV
			NETWORK FILE NAME			B	035483	-	