



ISOSTATIC
LEADERS IN BRONZE BEARINGS...and MORE

Isostatic Industries, Inc.
4153 North Kostner Avenue
Chicago, IL 60641
Toll Free: 800.621.5500
Phone: 773.286.3444
Fax: 773.282.3323
Email: info@isostatic.com

Item # 402236, Oilube® Powdered Metal Bronze SAE841 Flange Bearings - INCH

Isostatic Oilube® Bearings / Bushings

- Standard stock products
- SAE 841-copper (87-90%), tin (8-9), carbon, other elements
- Powdered metal bronze providing interconnected reservoirs for oil
- Vacuum impregnated with SAE 30 oil during the manufacturing process (approx. 19% by vol.)
- Self-lubricating – when in motion oil rises to the surface for lubrication and restores itself when at rest
- Ideal for heavy loads at moderate speeds or light loads at high speeds – max Pv 50,000, P-Load 2,000, V-SFM-1,200
-

[+ more](#)



[Description](#) | [Specifications](#) | [Dimensions](#) | [Tolerances](#) | [Performance Data](#)

Description

Detailed Description

.627 IN I.D. x .753 IN O.D. x 5/8 IN Length x 1 IN Flange O.D. x 1/8 IN Flange Thick, SAE 841 Powdered Metal Bronze, Flange Bearing

Specifications

Catalog Number	BSF-2024-10
Interchange #	BSF202410 BSF2024-10
Unit of Measure	Each
Material	Powdered Metal / Oil Impregnated Bronze
Material Standard	SAE 841

Avg Unit Weight	0.0304 lb
UPC Code	00846802071912

Dimensions

Nominal Inner Diameter	5/8 in
Nominal Outer Diameter	3/4 in
Nominal Length	5/8 in
Flange Nominal Outer Diameter	1 in
Flange Nominal Thickness	1/8 in

Tolerances

Inner Diameter Tolerance	+ .000, - .001 in
Outside Diameter Tolerance	+ .000, - .001 in
Overall Length Tolerance	± .005 in
Flange Diameter Tolerance	± .005 in
Flange Thickness Tolerance	± .005 in

Performance Data

Load - P Max Value	2,000 lb/in ²
Speed - V Max Value	1,200 ft ² /min
Load at Speed - PV Max Value (P.S.I. / S.F.M.)	50,000