



IPL1/0-3 SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPL1/0-3	3	2.24
IPL1/0-4	4	2.89
IPL1/0-5	5	3.54
IPL1/0-6	6	4.19
IPL1/0-8	8	5.49

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.

CONTACT NSI FOR SALES @ 800.321.5847

		<b>POLARIS</b> SALES CO. INC				
PROPRIETARY AND CONFIDENTIAL		11625 PROSPEROUS DRIVE ODESSA, FL 33556				
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.		<b>TITLE:</b> INSULATED 1/0 CONNECTOR				
<b>DWG. NO.</b> IPL1/0 SERIES	<table border="1"> <tr> <th>NAME</th> <th>DATE</th> </tr> <tr> <td>L. HILL</td> <td>07/14/10</td> </tr> </table>	NAME	DATE	L. HILL	07/14/10	
NAME	DATE					
L. HILL	07/14/10					
<b>MATERIAL:</b> N/A		<b>SCALE:</b> N/A				
		<b>SHEET:</b> 1 OF 1				