

WIRE MANAGEMENT

Thin-Wall Tubing

Easy-Splice™

TWHS Series Cnt'd



SPECIFICATIONS

- UL Recognize.
- Temperature Rating: 125 °C. 600V Max.
- Black, White and colored thin-wall tubing meet MIL-DTL-23053/5, Class 1.
- Clear meets MIL-DTL-23053/5, Class 2 and is not flame retardant.

FEATURES

- Flexible flame-retardant, thin wall, general purpose heat-shrinkable polyolefin tubing has a 2:1 shrink ratio.
- Used for electrical insulation, wire harness bundling, wire jacket marking and color coding, it also splices and makes functional terminations.
- Standard packaging is either 6" lengths in blister boxes, or in economical 25' spools.

CAT.NO.	EXPANDED I.D.	RECOVERED I.D.	NOMIINAL RECOVERED WALL THICKNESS	LENGTH (IN/FT)	STD. CTN. QTY.
TWHS-312-6	0.312	0.156	0.025	6"	10
TWHS-312-48	0.312	0.156	0.025	48"	1
TWHS-312	0.312	0.156	0.025	200' Spool	1
TWHS-375-6	0.375	0.187	0.025	6"	9
TWHS-375-48	0.375	0.187	0.025	48"	1
TWHS-375-25B	0.375	0.187	0.025	25' Spool	1
TWHS-375	0.375	0.187	0.025	200' Spool	1
TWHS-500-6	0.500	0.250	0.025	6"	8
TWHS-500-48	0.500	0.250	0.025	48"	1
TWHS-500-25B	0.500	0.250	0.025	25' Spool	1
TWHS-500	0.500	0.250	0.025	200' Spool	1
TWHS-750-6	0.750	0.375	0.030	6'	6
TWHS-750-48	0.750	0.375	0.030	48'	1
TWHS-750-25B	0.750	0.375	0.030	25' Spool	1
TWHS-750-25W	0.750	0.375	0.030	25' Spool	1
TWHS-750	0.750	0.375	0.030	100' Spool	1
TWHS-1000-6	1.000	0.500	0.035	6"	4
TWHS-1000-48	1.000	0.500	0.035	48"	1
TWHS-1000-25B	1.000	0.500	0.035	25' Spool	1
TWHS-1000	1.000	0.500	0.035	100' Spool	1
TWHS-1500-48	1.500	0.750	0.040	48"	1
TWHS-1500-25B	1.500	0.750	0.040	25' Spool	1
TWHS-2000-48	2.000	1.000	0.045	48"	1
TWHS-2000-25B	2.000	1.000	0.045	25' Spool	1