

CABLE TIES

Standard (Natural) Cable Ties

Standard - Natural Series



SPECIFICATIONS

- cULus Listed for Positioning Devices. UL62275.
- **Temperature Rating:** Min., -40°F to Max., 185°F (-40°C to 85°C)
- **Ideal Storage:** 23°C, Humidity 50%, Avoid storing cable ties next to warm objects.
- **Type 21 AH-2:** "Suitable for use in air-handling spaces (Plenums)".

FEATURES

- Designed for quick and easy use.
- Strong and flexible, they can be wrapped around a bundle quickly and the tail is easily inserted into a self-locking head.
- The smaller standard size ties have bent tails to facilitate insertion by user.
- Made of high-strength Nylon 66 that resists abrasion and chemicals such as common oils, greases, solvents, dilute acids and alkalines.
- Fungus-resistant, self-extinguishing and have excellent dielectric properties.

CAT. NO.	MAX. WIRE/CABLE SIZE (L)	MAX BUNDLE DIAMETER	TENSILE STRENGTH	LENGTH (IN.)	WIDTH (IN.)	STD. PKG. QTY.	STD. CTN. QTY.
1140	11"	3.300	40 Lbs.	11.500	0.140	100	2,000
1140X	11"	3.300	40 Lbs.	11.500	0.140	1000	2,000
1150	11"	2.940	50 Lbs.	11.100	0.189	100	2,000
1150X	11"	2.940	50 Lbs.	11.100	0.189	1000	2,000
1175	11"	2.940	75 Lbs.	11.100	0.189	100	2,000
11120	11"	3.000	120 Lbs.	11.500	0.300	100	2,000
1450	14"	4.070	50 Lbs.	14.100	0.189	100	3,000
1450X	14"	4.070	50 Lbs.	14.100	0.189	1000	3,000
1475	14"	4.070	75 Lbs.	14.100	0.189	100	3,000
14120	14"	4.070	120 Lbs.	14.250	0.300	100	2,000
15250	15"	4.375	250 Lbs.	15.000	0.500	50	500
1850	18"	5.070	50 Lbs.	18.000	0.189	100	2,000
18175	18"	5.250	175 Lbs.	17.750	0.315	50	500
18250	18"	5.500	250 Lbs.	18.870	0.500	50	500
22250	22"	6.875	250 Lbs.	22.87	0.500	50	500
24175	24"	7.140	175 Lbs.	24.000	0.345	50	500
28250	28"	8.875	250 Lbs.	28.75	0.500	50	500
30175	30"	9.250	175 Lbs.	30.000	0.354	50	500
36175	36"	11.000	175 Lbs.	36.000	0.350	50	500
48175	48"	15.000	175 Lbs.	48.000	0.354	50	500

CABLE TIES