

CABLE TIES Standard (Natural) Cable Ties



FEATURES

- Designed for quick and easy use.
- Strong and flexible, they can be wrapped around a bundle quickly and the tail is easily inserted into a self-locking head.
- The smaller standard size ties have bent tails to facilitate insertion by user.
- Made of high-strength Nylon 66 that resists abrasion and chemicals such as common oils, greases, solvents, dilute acids and alkalines.
- Fungus-resistant, self-extinguishing and have excellent dielectric properties.

RATINGS



LISTED
Positioning Devices
UL62275

TEMPERATURE RATINGS:

Min., -40°F to Max., 185°F (-40°C to 85°C)

IDEAL STORAGE:

23°C, Humidity 50%, Avoid storing cable ties next to warm objects

TYPE 21 AH-2:

"Suitable for use in air-handling spaces (Plenums)"

MAX. WIRE/ CABLE SIZE (L)	CAT. NO.
4"	418
	418X
	450
5"	518
	518X
	540
	540X
6"	650
	650X
7"	750
	750X
	818
	818X
8"	840
	840X
	850
	850X
	875
	8120
	8120X
11"	1140
	1140X
	1150
	1150X
	1175
	11120
14"	1450
	1450X
	1475
15"	14120
	15250
18"	1850
	18175
	18250
22"	22250
24"	24175
28"	28250
30"	30175
36"	36175
48"	48175
60"	60175



MAX BUNDLE DIAMETER	TENSILE STRENGTH	LENGTH (IN.)	WIDTH (IN.)	STD. PKG. QTY.	STD. CTN. QTY.
0.800	18 Lbs..	4.000	0.095	100	5,000
0.800	18 Lbs..	4.000	0.095	1000	5,000
0.800	50 Lbs..	4.000	0.095	100	5,000
1.430	18 Lbs..	6.000	0.095	100	5,000
1.375	18 Lbs..	5.500	0.100	1000	5,000
1.300	40 Lbs..	5.500	0.140	100	3,000
1.300	40 Lbs..	5.000	0.140	1000	3,000
1.320	50 Lbs..	6.250	0.181	100	3,000
1.320	50 Lbs..	6.300	0.181	1000	3,000
1.810	50 Lbs..	7.500	0.189	100	3,000
1.810	50 Lbs..	7.500	0.189	1000	3,000
2.060	18 Lbs..	8.000	0.095	100	3,000
2.060	18 Lbs..	8.000	0.095	1000	3,000
2.060	40 Lbs..	8.000	0.140	100	3,000
2.060	40 Lbs..	8.000	0.140	1000	3,000
1.940	50 Lbs..	8.000	0.189	100	3,000
1.940	50 Lbs..	8.000	0.189	1000	3,000
1.940	75 Lbs..	8.000	0.189	100	3000
2.000	120 Lbs..	8.000	0.300	100	2,000
2.000	120 Lbs..	8.000	0.300	1000	2,000
3.300	40 Lbs..	11.500	0.140	100	2,000
3.300	40 Lbs..	11.500	0.140	1000	2,000
2.940	50 Lbs..	11.100	0.189	100	2,000
2.940	50 Lbs..	11.100	0.189	1000	2,000
2.940	75 Lbs..	11.100	0.189	100	2,000
3.000	120 Lbs..	11.500	0.300	100	2,000
4.070	50 Lbs..	14.100	0.189	100	3,000
4.070	50 Lbs..	14.100	0.189	1000	3,000
4.070	75 Lbs..	14.100	0.189	100	3,000
4.070	120 Lbs..	14.250	0.300	100	2,000
4.375	250 Lbs..	15.000	0.500	50	500
5.070	50 Lbs..	18.000	0.189	100	2,000
5.250	175 Lbs..	17.750	0.315	50	500
5.500	250 Lbs..	18.870	0.500	50	500
6.875	250 Lbs.	22.87	0.500	50	500
7.140	175 Lbs..	24.000	0.345	50	500
8.875	250 Lbs.	28.75	0.500	50	500
9.250	175 Lbs..	30.000	0.354	50	500
11.000	175 Lbs..	36.000	0.350	50	500
15.000	175 Lbs..	48.000	0.354	50	500
18.250	175 Lbs..	59.000	0.354	50	500