

COMPRESSION CONNECTORS

Dual Rated Meter Socket Lugs

CAL SERIES



FEATURES

- Made of dead-soft EC grade aluminum.
- 840 common dies – one die installs on all sizes.
- For aluminum or copper conductors.
- Pre-filled with oxide inhibitor.
- Installing dies (color red): .840, 18, 324, TX, 76, 11A, 249.

RATINGS

Max ampacity is based on NEC 310.15, insulation type, and conductor material. Please consult your current NEC manual.

RATING:
600V.

All dimensional data is listed in inches.

CAT. NO.
CAL4
CAL2
CAL1-48
CAL10
CAL20
CAL20-48
CAL30-48
CAL 40
CAL40-48



STRANDED	CONDUCTOR		BOLT SIZE	LENGTH (L)	WIDTH (W)	TANG LENGTH (A)	STD. CTN. QTY.
	SOLID	COMPACT					
4	3	4	3/8	3.250	0.3125	1.3125	12
2	1	2	3/8	3.250	0.3125	1.3125	12
1	1/0	1	1/2	3.250	0.3125	1.3125	12
1/0	2/0	1/0	3/8	3.250	0.3125	1.3125	12
2/0	3/0	2/0	3/8	3.250	0.3125	1.3125	12
2/0	3/0	2/0	1/2	3.250	0.3125	1.3125	12
3/0	4/0	3/0	1/2	3.250	0.3125	1.3125	12
4/0	-	4/0	3/8	3.250	0.3125	1.3125	12
4/0	-	4/0	1/2	3.250	0.3125	1.3125	12

