

CABLE TIES Releasable & Stainless Steel Ties -R, SS SERIES



RELEASABLE




- Releasable ties are manufactured from either natural Nylon 66 or Weather Resistant Nylon 66, these ties can be easily released and re-used.

TEMPERATURE RATING:

-40 °C to 85 °C (-40 °F to 185 °F).

MAX. WIRE/CABLE SIZE	CAT. NO.	MAX. BUNDLE DIA.	MIN. TENSILE STRENGTH	LENGTH (IN.)	WIDTH (IN.)	STD. PKG. QTY.	STD. CTN. QTY.
8"	850-R	2.000	50 Lbs.	8.00	0.210	100	1,000

STAINLESS STEEL CABLE TIES



- Made of Grade 304 stainless steel and are ideally suited for hazardous environments.
- Roller-ball design that is self locking, fast and easy to install.
- Smooth edges will not damage wires.
- Installation by hand or with a tool.
- Available with a non-toxic, halogen-free polyester coating in a wide choice of colors.
- Available in Grade 316, for applications that require extremely high corrosion resistance. To order 316SS material, add suffix "-316" to part number.

TEMPERATURE RATING:

-80 °C to 538 °C (-62.2 °F to 281.1 °F).

TRUE PLENUM RATING

Air handling ties approved for indoor use in air handling spaces and plenums and ducts per NFPA-1993.

MAX. WIRE/CABLE SIZE	CAT. NO.	MAX. BUNDLE DIA.	MIN. TENSILE STRENGTH	LENGTH (IN.)	WIDTH (IN.)	STD. PKG. QTY.	STD. CTN. QTY.
8"	SS8100	1.970	100 Lbs.	8.000	0.181	100	500
14"	SS14100	3.940	100 Lbs.	14.000	0.181	100	500
	SS14250	3.940	250 Lbs.	14.000	0.311	100	500
20"	SS20100	5.900	100 Lbs.	20.5	0.181	100	500
	SS20250	5.900	250 Lbs.	20.5	0.311	100	500
26"	SS26250	7.870	250 Lbs.	26.5	0.311	100	500