



Box mount, die cast aluminum with built-in junction box and sturdy mounting lugs. Medium base socket, 1/2" or 3/4" NPS hub size and a variety of globes. Incandescent lamp A21 for 100 Series, P525 for 200 Series. Lamp not supplied.

Color: White

Weight: 1.7 lbs

|                     |              |
|---------------------|--------------|
| <b>Project:</b>     | <b>Type:</b> |
| <b>Prepared By:</b> | <b>Date:</b> |

| Lamp Info   |      | Ballast Info |     |
|-------------|------|--------------|-----|
| Type        | A21  | Type         | N/A |
| Watts       | 300W | 120V         | N/A |
| Shape/Size  | N/A  | 208V         | N/A |
| Base        | N/A  | 240V         | N/A |
| ANSI        | N/A  | 277V         | N/A |
| Hours       | N/A  | Input Watts  | N/A |
| Lamp Lumens | N/A  |              |     |
| Efficacy    | N/A  |              |     |

## Technical Specifications

### Compliance

#### UL Listed:

Suitable for wet locations. Suitable for use in dwellings. Suitable for use with 90°C supply wiring. Complies with UL Standard 1598. For non-hazardous locations where the lamp, socket and wiring require protection from rain, corrosive fumes, non-combustible dusts, moisture, non-explosive vapors and gases. For lamp base up installation only when outdoors.

### Construction

#### Globes:

Supplied with clear thermal shock resistant soda lime glass unless otherwise stated. Colored and white glass globes available. Unbreakable Permaglobes available in clear and in color.

#### No Guard or Globe Supplied:

### Electrical

#### Input Voltage:

120V

